

Direct Link

Cross reference

RoHS/LF P/N Search

Customer drawing search

3D model search

Application tooling

Services

Contact us

Distributor list

Price request

Order samples

Documentation


Free search

Search by category

Start > Search=211PC022S4149* > 211PC022S4149

211PC022S4149

211PC022S4149 : 2 Way coupling NM seal female housing



Customer Drawing

Assistant

Add to Favorites

Email Datasheet

Print Datasheet

FCI Brings You More

Contact our sales/technical support

Sample request

Price request

Specifications

Mating Half

General	Mechanical	Physical	Terminal 1 Type	Environmental	Other Features
General					
Application	Engine Compartment Connectors Component to Wire Wire to Wire				
Ways	2				
Coding version	Yellow				
Product Type	Housing				
Coding	Yes				
Features	Circumferential interface seal Pre-assembled front grids support blade terminal guiding and mating Reduced size sealed housing Acceptable wire size range from 0.5 to 2 mm² Terminal position assurance (T.P.A.) and connection position assurance (C.P.A.) option available Female part can be used as an aggregate housing Sealing protection IP 68 - Rear sealing ensured by a pre-mounted mat-seal				
Hybrid	No				
Main Terminal family	SICMA				
Main Terminal size	1.5 mm				
Sealed	Yes				
Terminal Size	1.5				
Mechanical					
Connector mating force	< 60 N				
Physical					
Color	Yellow				
Material	PBT				
Temperature (Range)	-40°C to +125 °C				
Terminal 1 Type					
Terminal type 1	SICMA Female 1.5 mm Terminal				
Ways for Terminal Type 1	2				
Contact insertion force for Terminal Type 1	< 12 N				
Contact Pitch for Terminal Type 1	3.33 mm				
Retention force (Contact) for Terminal Type 1	> 100N				
Environmental					
IMDS	Yes				
Other Features					
Market	Passenger Vehicles				
Type	Female				
Part Situation	Active				
Disclaimer	Displayed data is for information purposes only. For more information, please contact your local sales office. The supply of some products might be limited to some customers.				