

Direct Link ...

- Cross reference
- RoHS/LF P/N Search
- Customer drawing search
- 3D model search
- Industry Standards

Services ...

- E-Services
- Distributor list
- Price request
- Order samples

Documentation ...

- Free search
- Search by category

Start > Search=61729-0010BLF* > 61729-0010BLF

61729-0010BLF
61729-0010BLF - USB
: Type B, Receptacle,
Through Hole, 30u GXT
Contact, 4 Pins, Full
Back Shield with Bright
Tin Plating, 1.57 mm
PCB, White HSG, Tube
packing

Add to Favorites

Print Datasheet

ACTIVE

Electronics division

FCI Brings You More

- Contact our sales/technical support
- Sample request
- Price request
- Check distributor stock



Specifications

Download document

General Dimensional Mounting Physical Approvals / Certifications Other Features

General

Hold Down Style	Standard
Number of contacts	4
Orientation	Right Angle
Pin Orientation	Standard
Product Type	Receptacle
Shell Options	Back Shield
Style	B Type
Sensor Contact Options	without Sensor Contact
Series Number	61729
Single or Dual Stack	Single

Dimensional

Thickness (Board - recommended)	1.57 mm
Thickness (Panel - max)	2.67 mm

Mounting

Mounting flange / Hole options	None
Mounting style	Through Hole

Physical

Color (Housing)	White
Material (Housing)	Glass - Fiber Filled Thermoplastic, UL 94V-0
Plating (Contact area)	30u" GXT
Plating (Shell)	Pure Tin / Nickel Under Plating
Plating (Tail)	100u" Pure Tin

Approvals / Certifications

USB 2.0 Qualified	Yes
-------------------	-----

Other Features

Packaging (Options)	Tubes
---------------------	-------