

**Direct Link** ...

Cross reference

RoHS/LF P/N Search

Customer drawing search

3D model search

Industry Standards

**Services** ...

E-Services

Distributor list

Price request

Order samples

**Documentation** ...

Free search

Search by category

Start > Search=61729-1010BLF\* > 61729-1010BLF

**61729-1010BLF**  
**61729-1010BLF - USB**  
**: Type B, Receptacle,**  
**Through Hole, 30u GXT**  
**Contact, 4 Pins, Full**  
**Back Shield with Bright**  
**Tin Plating, 1.57 mm**  
**PCB, Black HSG, Tube**  
**packing**



ACTIVE

Electronics division



Add to Favorites

Print Datasheet

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)
- [Check distributor stock](#)

Specifications

Download document

General   Dimensional   Mounting   Physical   Approvals / Certifications   Other Features

**General**

Hold Down Style	Standard
Number of contacts	4
Orientation	Right Angle
Pin Orientation	Standard
Product Type	Receptacle
Shell Options	Back Shield
Style	B Type
Sensor Contact Options	without Sensor Contact
Series Number	61729
Single or Dual Stack	Single

**Dimensional**

Thickness (Board - recommended)	1.57 mm
Thickness (Panel - max)	2.67 mm

**Mounting**

Mounting flange / Hole options	None
Mounting style	Through Hole

**Physical**

Color (Housing)	Black
Material (Housing)	Glass - Fiber Filled Thermoplastic, UL 94V-0
Plating (Contact area)	30u" GXT
Plating (Shell)	Pure Tin / Nickel Under Plating
Plating (Tail)	100u" Pure Tin

**Approvals / Certifications**

USB 2.0 Qualified	Yes
-------------------	-----

**Other Features**

Packaging (Options)	Tubes
---------------------	-------