



- Cross reference
- RoHS/LF P/N Search
- Industry Standards
- Alphabetical List
- 3D model search
- Customer drawing search
- Free search
- Search by category
- E-Services
- Distributor list

Start > Search=61729-1010R\* > 61729-1010RLF

61729-1010RLF

61729-1010RLF - USB : Type B, Receptacle, Through Hole, 30u GXT Contact, 4 Pins, Full Back Shield with Bright Tin Plating, 1.57 mm PCB, Black HSG, Tape and Reel packing

Customer drawing

Environmental Compliance Report

ACTIVE

RoHS Compliant

Add to Favorites

Print Datasheet

FCI Brings You More

Contact our sales/technical support

Sample request

Price request

Specifications

Download document

Approvals / Certifications

Dimensional

General

Mounting

Physical

Other Features

Approvals / Certifications

USB 2.0 Qualified	Yes
USB 3.0 Qualified	No

Dimensional

Thickness (Board - recommended)	1.57 mm
Thickness (Panel - max)	2.67 mm

General

<b>Hold Down Style</b>	Standard
<b>Number of contacts</b>	4
<b>Orientation</b>	Right Angle
<b>Pin Orientation</b>	Standard
<b>Product Type</b>	Receptacle
<b>Shell Options</b>	Back Shield
<b>Style</b>	B Type
<b>Sensor Contact Options</b>	without Sensor Contact
<b>Series Number</b>	61729
<b>Single or Dual Stack</b>	Single
<b>Mounting</b>	
<b>Mounting flange / Hole options</b>	None
<b>Mounting style</b>	Through Hole
<b>Physical</b>	
<b>Color (Housing)</b>	Black
<b>Material (Housing)</b>	Glass - Fiber Filled Thermoplastic, UL 94V-0
<b>Plating (Contact area)</b>	30u" GXT
<b>Plating (Shell)</b>	Pure Tin / Nickel Under Plating
<b>Plating (Tail)</b>	100u" Pure Tin
<b>Other Features</b>	
<b>Most Popular Configuration</b>	Not Applicable
<b>Packaging (Options)</b>	Tape and Reel

FCI copyrights 2007 - 2012 All rights reserved for all countries - Privacy Policy