

SPECIFICATIONS

Mechanical

Mating Force: 3.5kgf (7.71Lb) max.
Unmating Force: 1.0kgf(2.20Lb) min.
Durability: 5000 cycles.

Electrical


Voltage Rating: 30 V rms maximum.
Low Level Contact Resistance: 30 mΩ maximum initial for the Power (VBUS) and Ground (GND) contacts and 50 mΩ maximum for all other contacts .
Dielectric Withstanding Voltage: 100V AC (Rms.)
Insulation Resistance: 100MΩ min. at 100V DC.

Physical


Frame&Spacer: Thermoplastic, UL 94V-0 rated in Black
Inner Insulator: Thermoplastic, UL 94V-0 rated in Blue color
Contact and Shell: Copper alloy
Front Shell & Rear Shell & Finger: Stainless steel
Plating: See "ORDERING INFORMATION"
Operating Temperature: -20°C to +85°C

USB 3.0 A TYPE Connector

**Triple USB3.0 Series
 A Type, Right Angle T/H
 9 Pos.**



DRAWING



ORDERING INFORMATION

PRODUCT NO.:	UEA	1	1	2	3	- MHD1 -	4 F
Series Prefix	UEA						4=Soft Tray
USB 3.0 A TYPE							F=Lead Free
Termination Type							Modification Code
1=Right Angle Dip							
Contact Design Type							Contact Area Plated
1=Female Contact							3=30μ" Gold
No. of Pos							Profile Height
1= 9 Pos.							2=4.13 mm