

# Han-Eco 10B-HSM1-with SL-M32-glanded



| Part number        | 19 43 110 0252                           |
|--------------------|--|
| Specification      | Han-Eco 10B-HSM1-with SL-M32-<br>glanded |
| HARTING eCatalogue | https://b2b.harting.com/19431100252      |

Image is for illustration purposes only. Please refer to product description.

#### Identification

| Category                    | Hoods/Housings              |
|-----------------------------|-----------------------------|
| Series of hoods/housings    | Han-Eco <sup>®</sup> B      |
| Type of hood/housing        | Surface mounted housing     |
| Description of hood/housing | With integrated cable gland |

#### Version

| Size         | 10 B                 |
|--------------|----------------------|
| Version      | Side entry           |
| Cable entry  | 1x M32               |
| Locking type | Single locking lever |

#### Technical characteristics

| Limiting temperature                   | -40 +125 °C                                    |
|--|--|
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Number of relockings                   | ≥500   |
| Degree of protection acc. to IEC 60529 | IP66   |
| Clamping range                         | 13 21 mm                                       |

### Material properties

| Material (hood/housing) | Polyamide (PA) Fibre-glass reinforced |
|-------------------------|---------------------------------------|
| Colour (hood/housing)   | RAL 9005 (jet black)                  |
| Material (seal)         | NBR                                   |



# Material properties

| Colour (seal)  | RAL 9005 (jet black)                                   |
|--|--|
| Material (locking)   | Polyamide (PA) Fibre-glass reinforced                  |
| Colour (locking)   | RAL 9005 (jet black)                                   |
| Material flammability class acc. to UL 94                  | V-0  |
| Material flammability class acc. to UL 94 (locking levers) | V-0  |
| RoHS   | compliant with exemption                               |
| RoHS exemptions  | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status   | compliant with exemption                               |
| China RoHS   | 50   |
| REACH Annex XVII substances                                | Not contained  |
| REACH ANNEX XIV substances                                 | Not contained  |
| REACH SVHC substances                                      | Yes  |
| REACH SVHC substances                                      | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol<br>Lead   |
| ECHA SCIP number   | be45dcda-0f90-459a-a8bc-78fb7986a295                   |
| California Proposition 65 substances                       | Yes  |
| California Proposition 65 substances                       | Lead   |
| Fire protection on railway vehicles                        | EN 45545-2 (2020-08)                                   |
| Requirement set with Hazard Levels                         | R22 (HL 1-3)<br>R23 (HL 1-3)                           |

# Specifications and approvals

| Specifications | IEC 61984<br>EN 45545-2 Fire protection on railway vehicles |
|----------------|---|
| CE             | Yes   |

#### Commercial data

| Packaging size                 | 1  |
|--------------------------------|--|
| Net weight                     | 243 g                                    |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140178403                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |
|                                |  |