

PCB receptacle M L-cod (60pcs) W/O FE



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 21 03 396 1506 |
| Specification | PCB receptacle M L-cod (60pcs) W/O FE |
| HARTING eCatalogue | https://b2b.harting.com/21033961506 |

Identification

| | |
|----------------|-------------------------|
| Category | Connectors |
| Series | Circular connectors M12 |
| Identification | Power |
| Element | PCB adapter |
| Specification | Straight |

Version

| | |
|--------------------|------------------------------------|
| Termination method | Reflow soldering termination (THR) |
| Gender | Male |
| Shielding | Shielded |
| Number of contacts | 4 |
| Coding | L-coding |
| Details | Order housings separately |
| Pack contents | 60 pieces in a tray |

Technical characteristics

| | |
|-----------------------|---------------------------|
| Rated current | 16 A |
| Rated voltage | 63 V |
| Rated impulse voltage | 1.5 kV |
| Pollution degree | 3 |
| Overvoltage category | III |
| Insulation resistance | $>10^8 \Omega$ |
| Contact resistance | $\leq 10 \text{ m}\Omega$ |



Pushing Performance
Since 1945

Technical characteristics

| | |
|----------------------|----------------|
| Limiting temperature | -40 ... +85 °C |
| Mating cycles | ≥100 |
| Isolation group | I (600 ≤ CTI) |

Material properties

| | |
|---|------------------------|
| Material (insert) | Polyamide (PA) |
| Colour (insert) | Black |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Au over Ni Mating side |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| | |
|----------------|--|
| Specifications | IEC 61076-2-111 |
| UL / CSA | UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079 |
| PROFINET | Yes |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 60 |
| Net weight | 10 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140228429 |
| eCl@ss | 27460201 PCB connector (board connector) |