




- Notes 1 Rotation examples of ref. No. ⑨ to ref. No. ① is shown.
2 The recommended clamp torque of ref. No. ⑨ : 3 N·m.
LOCTITE 243, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ⑨ from loosening.
3 The direction of solder cup ref.No. ② is an example.
4 This products to be used with cable clamp JR13WCC-※(72)
※ designate diameter of applicable cable.
5 The cable pull and twisting strength, waterproof tightness and other characteristisc may differ,
depending on the cable structure.
Please confirm before the use.

5	POLYACETAL	(WHITE)				
4	DIALLYL PHTHALATE	(BLACK)	UL94V-0	9	ZINC ALLOY	CHROME PLATING
3	DIALLYL PHTHALATE	(BLACK)	UL94V-0	8	SIRICONE RUBBER	(BLACK)
2	PHOSPHOR BRONZE	SILVER PLATING 3 μm min.		7	BRASS	CHROME PLATING
1	ZINC ALLOY	CHROME PLATING		6	SIRICONE RUBBER	(RED)
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS

<div>UNITS mm</div>		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE

<div>HRSHIROSE ELECTRIC CO., LTD.</div>	APPROVED	: HY. KOBAYASHI	16. 02. 23	DRAWING NO.	EDC-111150-71-00
	CHECKED	: HY. KOBAYASHI	16. 02. 23	PART NO.	RM15WTPZ-3P(71)
	DESIGNED	: HT. ZENBA	16. 02. 23	CODE NO.	CL109-1622-1-71
	DRAWN	: HT. ZENBA	16. 02. 23		

	1	1
---	---	---