



May.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.








PANEL CUTOUT DIMENSIONS








CODE NO.	NUMBER OF CONTACT	A	B	C	D	E
541-0943-0	2	8.0	2.5	15.0	8.4	11.9
541-0944-3	3	10.5	5.0	17.5	10.9	14.4
541-0945-6	4	13.0	7.5	20.0	13.4	16.9
541-0946-9	5	15.5	10.0	22.5	15.9	19.4
541-0947-1	6	18.0	12.5	25.0	18.4	21.9
541-0948-4	7	20.5	15.0	27.5	20.9	24.4
541-0949-7	8	23.0	17.5	30.0	23.4	26.9
541-0950-6	9	25.5	20.0	32.5	25.9	29.4
541-0951-9	10	28.0	22.5	35.0	28.4	31.9

APPLICABLE PANEL THICKNESS(t)	X
1.7-2.0	1.5
1.3-1.6	1.0
0.9-1.2	0.5
0.7-0.8	0

HRS DRAWING FOR REFERENCE







NOTES 1 : SHOWS CONFIGURATION OF THE MATING FACE FOR 2, 3, 4 AND 5 POS.
2 : INDICATED CONFIGURATION IS APPLICABLE TO 6 POS , AND HIGHER CONTACT POSITIONS.
3 : INDICATED CONFIGURATION IS APPLICABLE TO 8 POS , AND HIGHER CONTACT POSITIONS.
4 : USE THE SHARP EDGE FOR ENGAGEMENT WITH THE PANEL.

NO.	MATERIAL	FINISH , REMARKS
1	POLYAMIDE	WHITE(NATURAL), UL94V-0

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1					

HIROSE ELECTRIC CO., LTD.

APPROVED	TS. SAKATA	10. 02. 16
CHECKED	TS. FUKUSHIMA	10. 02. 16
DESIGNED	HT. SATO	10. 02. 10
DRAWN	YK. NAKATSU	10. 02. 09

DRAWING NO. EDC3-161949-02
PART NO. DF1E-*EP-2.5C
CODE NO. CL541-
1/1