

Jun.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2		3		4																									
A		B		C		D																									
		Notes 1 This product is delivered disassembled. 2 The recommended clamp torque of Ref.No. ① to be 2 to 2.5N · m. LOCTITE 263, Henkel Japan or equivalent is recommended to prevent Ref.No. ① from loosening. 3 The cable pull and twisting strength and other characteristics may differ, depending on the cable structure. please before the use.																													
		<table border="1"><tr><td>2</td><td>POLYPHENYLENE SULFIDE</td><td>(BLACK)</td><td>UL94V-0</td><td></td><td></td><td></td><td></td></tr><tr><td>1</td><td>BRASS</td><td>BLACK CROME PLATING</td><td></td><td>3</td><td>ACRYLONITRILE BUTADIENE RUBBER</td><td>(GRAY)</td><td></td></tr><tr><td>NO.</td><td>MATERIAL</td><td colspan="2">FINISH . REMARKS</td><td>NO.</td><td>MATERIAL</td><td colspan="2">FINISH . REMARKS</td></tr></table>						2	POLYPHENYLENE SULFIDE	(BLACK)	UL94V-0					1	BRASS	BLACK CROME PLATING		3	ACRYLONITRILE BUTADIENE RUBBER	(GRAY)		NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS	
		2	POLYPHENYLENE SULFIDE	(BLACK)	UL94V-0																										
		1	BRASS	BLACK CROME PLATING		3	ACRYLONITRILE BUTADIENE RUBBER	(GRAY)																							
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS																									
<table border="1"><tr><td>UNITS mm</td><td></td><td>SCALE 2 : 1</td><td>COUNT </td><td>DESCRIPTION OF REVISIONS</td><td>DESIGNED</td><td>CHECKED</td><td>DATE</td></tr></table>						UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE																		
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE																								
		HIROSE ELECTRIC CO., LTD.		APPROVED : HY. KOBAYASHI 18. 02. 26				DRAWING NO. EDC-110459-31-00																							
				CHECKED : HY. KOBAYASHI 18. 02. 26				PART NO. JR13WCCA-10(31)																							
				DESIGNED : TH. KAMEYA 18. 02. 24				CODE NO. CL114-2075-1-31																							
				DRAWN : MK. INOUE 18. 02. 14				1/1																							

FORM HC0011-5-51