




ELV, RoHS COMPLIANT






NOTE1. APPLICABLE CONNECTOR : GT17H-4S/SET(C)
GT17HS-4S/SET(C)
2. APPLICABLE PC BOARD : T=1.6mm


MATED CONNECTORS

3	COPPER ALLOY	TIN PLATING	5	PS	
2	BRASS	TIN PLATING	4	PS	
1	PPS	BLUE			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED CHECKED DATE
HIROSE ELECTRIC CO., LTD.		APPROVED : AR. SHIRAI	10.12.28	DRAWING NO.	EDC3-167222-00
		CHECKED : AR. SHIRAI	10.12.28	PART NO.	GT17H-4P-2DS(C)
		DESIGNED : NH. NAKATA	10.12.28	CODE NO.	CL767-0212-4-00
		DRAWN : NH. NAKATA	10.12.28		1/2

May.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



PACKAGE STYLE



Package style

1. 300 PCS. / REEL
2. TOP COVER TAPE PEEL FORCE TO BE 0.1 TO 0.7 N AFTER SEALING.

HRS

DRAWING NO.	EDC3-167222-00
PART NO.	GT17H-4P-2DS(C)
CODE NO.	CL767-0212-4-00

2/2