




Quality Products. Service Excellence.

Hard Wired 170E Series



Features

- Single winding, does not provide isolation, for use where equipment is already isolated and only voltage change is required.
- Flexible world wide applications, 50 or 60 Hz. operation, step down (230VAC to 115 VAC) or step up (115VAC to 230VAC).
- Totally enclosed rear case, includes handy internal grounding bolt.
- Extra vacuum varnish for use in high humidity.
- Includes a rear mounted (but not wired), standard 115VAC, 3-wire receptacle.
- Enclosed case with convenient knockouts and includes two cable clamps allowing for easy wire connections.
- Models 170SE, 170AE, 170BE, 170CE & 170DE are CSA certified (209651)
- Connection by flexible leads, 8" minimum length
- Remember - These units do NOT convert line frequency



| Part No. | Capacity | Overall Dimensions |      |      |      |      | Weight |
|----------|----------|--------------------|------|------|------|------|--------|
|          | VA       | A                  | B    | C    | D    | E    | Lbs    |
| 170SE    | 50       | 3.13               | 4.00 | 4.10 | 2.30 | 3.10 | 3.5    |
| 170AE    | 100      | 3.13               | 4.00 | 4.10 | 2.30 | 3.10 | 4      |
| 170BE    | 200      | 3.13               | 4.30 | 4.10 | 2.30 | 3.40 | 5      |
| 170CE    | 300      | 3.13               | 4.80 | 4.10 | 2.30 | 3.90 | 6.5    |
| 170DE    | 500      | 3.75               | 5.00 | 4.90 | 2.80 | 4.10 | 10     |
| 170EE    | 750      | 3.75               | 6.00 | 4.90 | 2.80 | 5.10 | 15     |
| 170FE    | 1000     | 3.75               | 6.00 | 4.90 | 2.80 | 5.10 | 15.5   |
| 170GE    | 1500     | 4.38               | 7.00 | 5.50 | 3.30 | 5.90 | 23.5   |
| 170JE    | 2000     | 4.38               | 7.00 | 5.50 | 3.30 | 5.90 | 24     |

Tags: autotransformer, line transformer, hard wired, single winding, voltage change, step down, step up Data subject to change without notice

