




Top View of Assembly




SECTION A-A End View of Assembly




SECTION B-B Side View of Assembly




Top View Looking Inside Box



Flanged Lid



SECTION C-C Side of Slot



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory mjm@hammondmfg.com for quotes
Solid models of this enclosure available in STEP or IGES.

NOTE

Purchased assembly includes box, lid and 4 cover screws.
Box and lid are made from Diecast Aluminum Alloy.
Silicone Gasket supplied with liquid resistant enclosure.

PART NUMBERS

1590GFL Enclosure	
Natural Finish Enclosure	1590GFL
Black Textured Enclosure	1590GFLBK
1590GFL Liquid Resistant Enclosure (Silicone Gasket)	
Natural Finish Enclosure	1590W GFL
Black Textured Enclosure	1590W GFLBK
ACCESSORIES	
Recommended Torque: 75 ozf.in / 55 cN.m	
Liquid Resistant Cover Screws	
Stainless Steel Cover Screws (Pkg 100) [6-32 x 1/2" With O-Ring]	1590WMS100
Black Stainless Steel Cover Screws (Pkg 100) [6-32 x 1/2" With O-Ring]	1590WMS100BK
Standard Cover Screws	
Plated Cover Screws (Pkg 100) [6-32 x 1/2"]	1590MS100
Black Cover Screws (Pkg 100) [6-32 x 1/2"]	1590MS100BK

Dimensions:
mm
[inches]

HAMMOND
MANUFACTURING™
1590GFL
www.hammondmfg.com