


RF TERMINATION Type 65_4310-50-0-Z1

Description

Standard Termination, Low Power

QuickLock Interface



Product Configuration

Connector	4.3-10 plug (male)
Interface standards	IEC 61169-54

Technical Data

Electrical Data

Nominal Impedance	50 Ω
Frequency range	0 to 4 GHz
Frequency sub range	DC to 2 GHz 2 to 4 GHz
VSWR max.	1.06 1.1
Power rating	2 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.

Mechanical Data

Matings	100
---------	-----

Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-40 °C to 130 °C compliant
--	-------------------------------

Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Silver Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00330791
-----------------	--------------

Ordering Information

Single Packaging Packaging	65_4310-50-0-Z1/033_-E
-------------------------------	------------------------