CLSXB8T

Overview

MICRO SWITCH CLSX Series Explosion-proof Cable Pull Safety Switch, 2NC Direct Opening, Slow Action, Explosion-proof, 1/2 NPT, Silver Contacts.
The CLSX Series Cable Pull Safety Limit Switch is designed to provide e...

View More

Technical Specifications

Product Type	**Cable Pull Safety Switch**		Actuator	**Cable, Maintained**
Switch Type	**2NC Direct Opening, Slow Action**		Contact Material	**Silver**
Termination Type	**1/2 NPT**		Ampere Rating	**100 mA to 10 A (Thermal)**
Voltage	**600 Vac and 250 Vdc max.**		Housing Material	**Aluminum**
Housing Type	**Explosion-proof**		Series Name	**CLSX**

View More

View documents in: English ▾

Documents

TITLE	DOCUMENT TYPE	LANGUAGE	SIZE
📄 **PK 80026: Explosion-proof Momentary Cable Pull Limit Switch**	Installation Instructions	English	155KB
📄 **PK 81593: CLSX Series Explosion-proof Maintained Cable Pull Limit Switch**	Installation Instructions and Approvals Documentation	English	162KB
📄 **MICRO SWITCH Safety Switches Comparison**	Product Range Guide	English	504KB
📄 **MICRO SWITCH Switches in Conveyor Applications**	Application Note	English	176KB

View More

Product Features

- Positive opening operation of normally closed contacts
- Available with up 2NC positive opening contacts
- Broken/slacked cable detection
- UL, CSA

Applications

- Conveyor lines in hazardous atmospheres