

OPA-Q

(Home : Products : Sw itches : MICRO SWITCH™ Limit Sw itches : MICRO SWITCH™ Global Limit Sw itches : OP)

Image Not Available

Enclosed Switch Series OP: Overtravel Top Plunger, 1NO 1NC Snap Action SPDT, High capacity

Actual product appearance may vary.

Product Specifications

Availability	Global
Operating Force (OF)	8,90 N [2.0 lb] max.
Release Force	2,22 N [0.50 lb] min.
Pretravel (PT)	1,27 mm [0.05 in] max.
Overtravel (OT)	3,18 mm [0.125 in] min.
Differential Travel (DT)	0,23 mm [0.009 in] max.
Product Type	Enclosed Sw itches
Actuator	Top Plunger
Lever Type	None
Circuitry	1NC 1NO Snap Action, SPDT
Ampere Rating	20 A
Supply Voltage	125 Vac, 250 Vac, 480 Vac
Housing Material	Aluminum Die-Cast
Termination Type	0.5 in - 14NPT Conduit
Series Name	OP
Sealing	NEMA 1, 3, 4, 13
UL File #	E12252
Comment	High capacity.
Agency Approvals and Standards	UL, CSA
UNSPSC Code	39122213
UNSPSC Commodity	39122213 Limit Sw itches