



🏠 [Electronics Tapes](#)

Products	Solutions	Where To Buy
----------	-----------	--------------

[Product Catalog for Electronic Materials](#) > [Interconnect Solutions](#) > [3M™ Interconnect Solutions](#) > [3M™ Application Tools & Accessories](#) > [3M™ Strain Reliefs](#) > [3M™ Accessories](#) >

3M™ Accessories, 3448-3030



[\[click to enlarge\]](#)

.100" Wiremount IDC Skt Accessories

The .100" X .100" EMI System Accessories fit existing 3M connectors. The spring latch attachment allows quick, easy connect/disconnect, and the intra-cabinet grounding eliminates pigtailed/drain wires and need for grounding clamps. It has a cast aluminum shell which offers excellent ground for EMI/ESD.

Product Information

Product / 3M Id / UPC

3M Id : 80-6101-5326-6
 GTIN(UPC/EAN) :

Characteristics

3M Logo, Position Indicator, Wire Gauge, Insulator Material	:3M Logo, Part Identification Number, Position 1
China RoHS - Below MCV	:Yes
Color	:Gray
Contact Material	:Copper Alloy
Electrical Current Rating	:1 A
Flammability	:UL 94V-0
Insulation Resistance	:> 1x10 ⁹ Ohm at 500 Vdc
Material	:Glass Filled Polyester (PBT)
RoHS 2011/65/EU Compliant	:Yes
Strain Relief Material	:Stainless Steel - .012 [0.30] thick
Temperature Rating	:-55 Degree C to +105 Degree C
Underplating and U-Slot	:100 micro inches [2.54 micro meter] Nickel-QQ-N-290, Class 2

Wiping Area (Plating Material)

.30 micro inches (0.76 micro meter) Gold-MIL-G-45204, Type II, Grade C

Wire Accommodation

:26 & 28 AWG Solid and Stranded

Withstanding Voltage

:1000 Vrms at Sea Level

 Documentation

Follow us:



Singapore

[Legal](#) | [Privacy](#) | [Full Site](#)

© 3M 2017. All Rights Reserved.