$3M^{{}^{\rm TM}}\,Serial\,Attached\,SCSI\,(SAS)\,Connector$

Boardmount Compliant Pin, Vertical Elevated Receptacle

A CONTRACTOR OF A CONTRACTOR O	 6 Gbps input/output connector for backplane applications Two contact mating levels for early-mate and late-break allows "blind mating" or "hot swap" applications Capable of accepting HDD fitted with SAS or Serial Advanced Technology Attachment (SATA) Header Compliant pins Elevated height gives more backplane space Compatible with drives compliant to SFF-8223, SFF-8323, and SFF-8523. Compliant to SFF-8482 Rev 2.2 Meets SAS Specification, SAS-2.0 See the Regulatory Information Appendix (RIA) in the "RoHS compliance" section of www.3Mconnector.com for compliance information (RIA E1 & C1 apply)
	Date Modified: March 10, 2010 TS-2177-C Sheet 1 of 3

Physical

Insulation:	
Material:	High Temperature Thermoplastic
Flammability:	UL94V-0
Color:	Black
Contact:	
Material:	Copper Alloy
Plating:	
Underplating:	50u" [1.27 µm] Min. Nickel
Wiping Area:	30u" [0.76 µm] Min. Gold
Solder Tails:	100u" [2.54 µm] Min. Matte Tin
Marking:	3M Logo

Electrical

Current Rating:Power Pin: 1.5 A
Signal Pin: 500 mAInsulation Resistance:103 MΩ min.Withstanding Voltage:500 V_{AC} at sea level

Environmental

Operating Temperature: $0^{\circ}C$ to $+55^{\circ}C$ **Non-Operating Temperature:** $-40^{\circ}C$ to $+85^{\circ}C$


UL File No.: E68080

Electronic Solutions Division Interconnect Solutions http://www.3Mconnector.com

$3M^{{}^{\scriptscriptstyle \mathsf{TM}}}\operatorname{Serial}\operatorname{Attached}\operatorname{SCSI}\left(\operatorname{SAS}\right)\operatorname{Connector}$

Boardmount Compliant Pin, Vertical Elevated Receptacle

SBR Series



Electronic Solutions Division Interconnect Solutions http://www.3Mconnector.com

ЗМ

3M is a trademark of 3M Company. For technical, sales or ordering information call 800-225-5373


$3M^{{}^{\scriptscriptstyle \mathsf{TM}}}\operatorname{Serial}\operatorname{Attached}\operatorname{SCSI}\left(SAS\right)\operatorname{Connector}$

Boardmount Compliant Pin, Vertical Elevated Receptacle

SBR Series

For technical, sales or ordering information call

800-225-5373



Electronic Solutions Division Interconnect Solutions http://www.3Mconnector.com

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



3M Electronics Solutions Division 6801 River Place Blvd. Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3Mconnector.com

Please recycle. Printed in USA. © 3M 2010. All rights reserved. RIA-2217B-E