



# Datasheet for part number M83513/28-D01NW

|                                                                                 |
|---------------------------------------------------------------------------------|
| Our Catalog Part Number: M83513/28-D01NW                                        |
| Our Global Manufacturing Part Number: M83513/28-D01NW                           |
| Brand: Cannon Product Category: Micro Product Line: Micros Series: M83513-10-33 |

| Product Datasheet               |                                                                              |
|---------------------------------|------------------------------------------------------------------------------|
| Series                          | Micro D Metal Shell - 0.050 inch spacing                                     |
| Slash Sheet                     | Connector, Plug, CBS, Sizes 9 to 37                                          |
| Arrangement                     | 25 Contact                                                                   |
| Contact Type                    | PC Tail                                                                      |
| Contact Material                | gold plated copper alloy                                                     |
| Contact Resistance              | 8 milliohms max.                                                             |
| Wire Length                     | 0.109" long, #24 AWG solid copper wire per QQ-W-343, Type "S", solder dipped |
| Shell Material                  | Aluminum                                                                     |
| Shell Finish                    | Electroless Nickel                                                           |
| Insulator                       | LCP                                                                          |
| Hardware                        | Jackpost and Threaded insert                                                 |
| Current Rating                  | 3 A max.                                                                     |
| Dielectric Withstanding Voltage | 600 VAC at sea level<br>150 VAC at 70,00' altitude                           |
| Insulator Resistance            | 5000 megohms min.                                                            |
| Thermal Shock                   | -55°/+125°                                                                   |
| Physical Shock                  | 50 G's, 3 axes, 6 milisecond duration sawtooth pulse                         |
| Vibration                       | 20G's, 10-2000 Hz. 12 hours                                                  |
| Durability                      | 500 cycles of mating and unmating, 500 CPH max.                              |
| Moisture Resistance             | Insulator resistance > 100 megohms                                           |
| SaltSpray                       | 48 hours                                                                     |