



[Home](#) | [Sign In](#) | [Contact Us](#)

SEARCH

Go



Standard D (Machined)



**PART NUMBER: DAMN15PNK87**

<b>Where Sold</b>	Europe, Asia Pacific, Americas
<b>Product Group</b>	D-Subminiature
<b>Product Sub-Family</b>	D-Sub Standard
<b>Component Type</b>	Connector
<b>Application Type</b>	Commercial
<b>Cable or PC Board</b>	PC Board
<b>Gender</b>	Plug
<b>Number of Signal Pins</b>	15
<b>Number of Size 8 contacts</b>	0
<b>Straight or Right Angle</b>	Straight
<b>Contact Plating</b>	Gold over Nickel
<b>Shell Plating</b>	Tin (with Grounding Dimples)
<b>Hardware</b>	Standoffs, 4-40 Screwlocks
<b>Contact Termination</b>	0,76 (.030) dia, 4,52 (.178) Extention
<b>Shell Size</b>	DA
<b>Temperature Rating</b>	-55°C to +125°C
<b>Current Capacity</b>	7.5 A
<b>Contact Resistance</b>	8 milli ohms max.
<b>Dielectric Withstanding Voltage</b>	1250 V AC at Sea Level
<b>Reference Industry Specifications</b>	Mil-PRF-24308
<b>Insulator Material</b>	Green Polyester UL 94V-0
<b>Contact Material</b>	Copper Alloy
<b>Shell Material</b>	Steel
<b>Hardware Material and Plating</b>	Steel, Tin Plated

Sales

Ask a

Prod

Stock

Dime  
Draw

PRI

[Home](#) | [About ITT](#) | [Products](#) | [Design Center](#) | [Literature](#) | [News & Events](#) | [Search Tools](#) | [G Support](#)

© ITT Corporation. All rights reserved. [Legal Disclaimer](#) | [Privacy Policy](#) | [General Terr Channel Partners Sign-In](#)