



[Home](#) | [Sign In](#) | [Contact Us](#)

SEARCH

Go



Powered by Cannon
Configurator Technology
Patents Pending

Standard D (Machined)

PART NUMBER: DEMAM9S

Where Sold	Asia Pacific, Europe, Americas
Product Group	D-Subminiature
Product Sub-Family	D-Sub Standard
Component Type	Connector
Application Type	Military/High Reliability
Cable or PC Board	Cable
Gender	Receptacle
Number of Signal Pins	9
Number of Size 8 contacts	0
Straight or Right Angle	Straight
Contact Plating	Gold over Nickel
Shell Plating	Yellow Chromate over Zinc
Hardware	3,05 (.120) Through Holes
Other Features	Metal Contact Retention Clips
Contact Termination	Crimp, Contacts Included
Shell Size	DE
Temperature Rating	-55°C to +125°C
Current Capacity	5 A

Sales Support

Ask a Specialist

Product Home

Stock Check

Dimensional
Drawing

PRINTABLE PAGE

Contact Resistance	8 milli ohms max.
Dielectric Withstanding Voltage	1250 V AC at Sea Level
Reference Industry Specifications	Mil-PRF-24308
Insulator Material	White (or Green) Polyester (or Dially Phthalate)
Contact Material	Copper Alloy
Shell Material	Steel

[Home](#) | [About ITT](#) | [Products](#) | [Design Center](#) | [Literature](#) | [News & Events](#) | [Search Tools](#) | [Global Sales Support](#)
© *ITT Corporation. All rights reserved.* [Legal Disclaimer](#) | [Privacy Policy](#) | [General Terms of Sale](#)
[Channel Partners Sign-In](#)