

KEMET Part Number: PHE850EF6470MF14R06L2
(F850FR474M300C)



Capacitor, Film, Metallized Polypropylene, 0.47 uF, +/-20% Tol, -55/+110C, Safety: Y2, 300 VAC, Lead Spacing=27.5 mm, Not For New Design, Please Check Possible Alternative Parts (AltPart)



General Information	
Supplier:	KEMET
Dielectric:	Metallized Polypropylene
Application:	Safety: Y2
Style:	Radial Box
Lead Form:	Wire Leads
Features:	Pulse
Approvals:	ENEC,UL,cUL
RoHS:	Yes

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	31.5	MAX
H	28	MAX
T	17.5	MAX
S	27.5	+/-0.4
LL	6	NOM
F	0.8	NOM

Specifications	
Capacitance:	0.47 uF
Voltage:	1250 VDC
Tolerance:	+/-20%
Voltage AC:	300 VAC
Rated Temperature:	110C
Temperature Range:	-55/+110C
Dissipation Factor @ 1 kHz:	0.15%
Dissipation Factor @ 10 kHz:	0.4%
Insulation Resistance:	21.28 GOhm
Maximum dVdT:	100 v/us
Miscellaneous:	Not For New Design, Please Check Possible Alternative Parts (AltPart)

Packaging Specifications	
Package Kind:	Bulk
Package Type:	Tray
Package Quantity:	126

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006-2016 IntelliData.net