


KEMET Part Number: F611DM106K100R

Film, Metallized Polyester, Commercial Grade, KEMET, F611, 10 uF, 10%, 100 V, 85C, Lead Spacing = 22.5mm



Dimensions

L	26mm MAX
H	18.5mm MAX
T	9mm MAX
S	22.5mm +/-0.4mm
H0	18.5mm +/-0.5mm
F	0.8mm +/-0.05mm
G	0.5mm NOM

Packaging Specifications

Packaging:	Ammo, 360x340x59mm, Box
Packaging Quantity:	300

General Information

Dielectric:	Metallized Polyester
Style:	Radial
Supplier:	KEMET
Series:	F611
Features:	MKT (Wound)
RoHS:	Yes
Lead:	Wire Leads
Miscellaneous:	The Rated Voltage Decreases 1.25%/C Between +85C And +105C (For +125C, Please Consult Kemet). ClimCat: 55/105/56

Specifications

Capacitance:	10 uF
Capacitance Tolerance:	10%
Voltage DC:	100 VDC, 75 VDC (105C)
Voltage AC:	63 VAC
Temperature Range:	-55/+105C
Rated Temperature:	85C
Dissipation Factor:	1.2% 1kHz
Insulation Resistance:	500 MOhms
Max dVdt:	5 V
Inductance:	6 nH