


C900AC SFTY X1-400 Y2-250, Ceramic, Safety, 3 pF, +/-0.25 pF, 400 VAC (X1), 250 VAC (Y2), COG, Lead Spacing = 10mm



**Dimensions**

<b>D</b>	7mm MAX
<b>T</b>	5mm MAX
<b>S</b>	10mm +/-1mm
<b>LL</b>	3.5mm +/-1mm
<b>F</b>	0.5mm +/-0.1mm

**Packaging Specifications**

<b>Packaging:</b>	Bulk, Bag
<b>Packaging Quantity:</b>	500

**General Information**

<b>Supplier:</b>	KEMET
<b>Series:</b>	C900AC SFTY X1-400 Y2-250
<b>Style:</b>	Radial Disc
<b>RoHS:</b>	Yes
<b>Termination:</b>	Tin
<b>Failure Rate:</b>	N/A
<b>Qualifications:</b>	UL, ENEC, VDE, CSA, CAN
<b>Halogen Free:</b>	Yes

**Specifications**

<b>Capacitance:</b>	3 pF
<b>Capacitance Tolerance:</b>	+/-0.25 pF
<b>Voltage AC:</b>	400 VAC (X1), 250 VAC (Y2)
<b>Dielectric Withstanding Voltage:</b>	2,600 V
<b>Temperature Range:</b>	-40/+125C
<b>Temperature Coefficient:</b>	COG
<b>Insulation Resistance:</b>	10 GOhms
<b>Quality Factor:</b>	460
<b>Safety Class:</b>	X1/Y2