


T330, Tantalum, MnO₂ Tantalum, Commercial Grade, 22 uF, 10%, 15 VDC, 2 Ohms, Lead Spacing = 5.08mm

C & D CASES




Dimensions

W	8.26mm +/-0.38mm
H	8.26mm +/-0.38mm
T	4.32mm +/-0.38mm
S	5.08mm +/-0.127mm
LL	12.7mm +/-3.18mm
F	0.64mm +/-0.03mm
E	1.57mm +/-0.25mm
G	0.38mm +/-0.13mm

Packaging Specifications

Packaging:	Bulk, Bag
Packaging Quantity:	200

General Information

Supplier:	KEMET
Series:	T330
Dielectric:	MnO ₂ Tantalum
Style:	Radial Molded
Description:	Radial, Solid Tantalum, Molded
Features:	Low Leakage
RoHS:	No
Prop 65:	 WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov .
REACH:	SVHC (Pb – CAS 7439-92-1)
Termination:	Lead (SnPb)
Construction:	Molded
Notes:	Longest Lead Is Positive
Shelf Life:	156 Weeks

Specifications

Capacitance:	22 uF
Capacitance Tolerance:	10%
Voltage DC:	15 VDC (85C), 10 VDC (125C), 0.15 VDC (125C Reverse)
Temperature Range:	-55/+125C
Dissipation Factor:	6.00%
Resistance:	2 Ohms (100kHz)
Leakage Current:	5 uA