


T340, Tantalum, MnO2 Tantalum, Commercial Grade, 1 uF, 10%, 50 VDC, 8 Ohms, Lead Spacing = 5mm




Dimensions

W	7.2mm MAX
H	8.3mm MAX
T	4mm MAX
S	5mm +/-0.5mm
LL	15mm +/-2mm
F	0.5mm +/-0.03mm

Packaging Specifications

Packaging:	Bulk, Bag
Packaging Quantity:	300

General Information

Series:	T340
Dielectric:	MnO2 Tantalum
Style:	Radial Molded
Description:	Radial, Solid Tantalum, Molded
RoHS:	No
Prop 65:	 WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov .
SCIP Number:	a3b4e2e1-63ea-439e-a89a-743225502a7d
Termination:	Lead (SnPb)
AEC-Q200:	No
Construction:	Molded
Miscellaneous:	Includes Standoff Height of 0.38 +/- 0.13mm.
Notes:	Longest Lead Is Positive.

Specifications

Capacitance:	1 uF
Capacitance Tolerance:	10%
Voltage DC:	50 VDC (85C), 33 VDC (125C), 0.5 VDC (125C Reverse)
Temperature Range:	-55/+125°C
Dissipation Factor:	6%
Resistance:	8 Ohms (100kHz)
Leakage Current:	1 uA