


KEMET Part Number: PEH536YEK3680M2
(A551HM681M450A)



PEH536, Aluminum Electrolytic, 680 uF, 20%, 450 VDC, -40/+105°C



General Information	
Series:	PEH536
Dielectric:	Aluminum Electrolytic
Description:	Snap-In, Aluminum Electrolytic
RoHS:	Yes
Lead:	2 Pin
AEC-Q200:	No
Component Weight:	135 g
Notes:	Add 0.5mm To D And 1mm To L For sleeving.
Shelf Life:	208 Weeks

Dimensions	
D	40mm +/-0.5mm
L	70mm +/-1mm
S	10mm +/-0.1mm
LL	6.3mm +/-1mm
F	2mm +/-0.1mm

Packaging Specifications	
Packaging:	Bulk, Bag
Packaging Quantity:	25

Specifications	
Capacitance:	680 uF
Capacitance Tolerance:	20%
Voltage DC:	450 VDC
Temperature Range:	-40/+105°C
Rated Temperature:	105°C
Life:	4600 Hrs (Rated Voltage And Ripple Current At 105C), 6000 Hrs (Rated Voltage At 105C)
Resistance:	110 mOhms (100Hz 20C), 61 mOhms (100kHz 20C)
Ripple Current:	2.7 Amps (100Hz 105C), 17.9 Amps (20kHz 40C)
Leakage Current:	918 uA (5min 20°C)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

