


T330, Tantalum, MnO2 Tantalum, Commercial Grade, 10 uF, 20%, 35 VDC, Lead Spacing = 5.08mm


C & D CASES**Dimensions**

W	8.26mm +/-0.38mm
H	8.26mm +/-0.38mm
T	4.32mm +/-0.38mm
S	5.08mm +/-0.127mm
LL	12.7mm +/-3.18mm
F	0.64mm +/-0.03mm
E	1.57mm +/-0.25mm
G	0.38mm +/-0.13mm

Packaging Specifications

Packaging:	Bulk, Bag
Packaging Quantity:	200

General Information

Series:	T330
Dielectric:	MnO2 Tantalum
Style:	Radial Molded
Description:	Radial, Solid Tantalum, Molded
Features:	Low Leakage
RoHS:	No
Prop 65:	 WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov .
SCIP Number:	a3b4e2e1-63ea-439e-a89a-743225502a7d
Termination:	Lead (SnPb)
AEC-Q200:	No
Construction:	Molded
Notes:	Longest Lead Is Positive.
Shelf Life:	156 Weeks

Specifications

Capacitance:	10 uF
Capacitance Tolerance:	20%
Voltage DC:	35 VDC (85C), 23 VDC (125C), 0.35 VDC (125C Reverse)
Temperature Range:	-55/+125°C
Dissipation Factor:	6%
Leakage Current:	5 uA