
## **KEMET Part Number: T350B475M016AT7301**

(T350B475M016ATTR)



Capacitor, Tantalum, General Purpose Radial Conformal (Dipped), 4.7 uF, +/-20% Tol, 16V@85C, Lead Spacing=2.54 mm



Dimensions (mm)			
Symbol	Dimension	Tolerance	
D	4.5		
Н	7.6		
F	0.5	+/-0.05	
S	2.54	+/-0.38	
LL	12.7	+/-1.26	

Packaging Specifications		
Package Kind:	T&R	
Package Quantity:	1500	

General Information		
Supplier:	KEMET	

Specifications		
Value:	4.7 uF	
Voltage DC @ 85C:	16V	
Voltage DC @ 125C:	10V	
Tolerance:	+/-20%	
Body Type:	Radial Conformal (Dipped)	
Temperature Range:	-55/+125C	
Application:	General Purpose	
Termination Type:	Tin (Sn)	
RoHS:	Yes	
Leakage Current:	0.6 uA	
Dissipation Factor:	5%	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

