

I-Temp eMMC – the perfect storage solution for harsh environment embedded applications.

Overview

Kingston[®] I-Temp *e*MMC[™] Flash memory offers JEDEC *e*MMC5.1 features and is backward compatible to earlier *e*MMC standards. It has all the advantages of standard *e*MMC plus the operating temperature range of the device meets industrial operating temperature requirements (-40°C~+85°C), which make it an ideal storage solution for outdoor, harsh environment and automotive applications.

Key Benefits

- Simplifies system design and reduces time to market. The standard interface makes fast-changing NAND technology invisible to the host and the host processor doesn't have to keep changing its software to accommodate every NAND technology change and variation. This helps to significantly reduce the design-in complexity and shorten the qualification cycle.
- Helps to improve whole system performance. The *e*MMC controller frees up the host processor's valuable resources from NAND management so the host processor can use its processing power on other tasks.
- Provides a cost-effective solution. As opposed to SLC NAND, eMMC uses MLC NAND so it makes higher capacity storage in
 embedded applications much more affordable and enables today's embedded designs to meet increasing demands for storage.
- Supports industrial operating temperature range (-40°C~+85°C)

I-Temp eMMC Part Numbers and Specifications

Part Number	Capacity	eMMC Standard	Package	NAND	Operating Temperature
EMMC04G-W627	4GB	5.0/5.1 (HS400)	11.5x13x1.0	MLC	-40°C~+85°C
EMMC16G-IB29	16GB	5.1 (HS400)	11.5x13x0.8	3D TLC	-40°C~+85°C
EMMC32G-IX29	32GB	5.1 (HS400)	11.5x13x0.8	3D TLC	-40°C~+85°C
EMMC64G-IX29	64GB	5.1 (HS400)	11.5x13x0.8	3D TLC	-40°C~+85°C
EMMC128-IX29	128GB	5.1 (HS400)	11.5x13x1.0	3D TLC	-40°C~+85°C

For more information, please visit kingston.com/emmc

Key Features

JEDEC Standard Features	eMMC 5.0	eMMC 5.1
Boot Operation		
Partitioning		
Sleep Mode		
Replay Protected Memory Block	\checkmark	\checkmark
Secure Trim/Secure Erase		
Hardware Reset		
Reliable Write		
Background Operation		
High Priority Interrupt		
DDR Interface		
Discard/Sanitize CMD		
Packed Commands, Context IDs		
Power OFF Notification		
Data Tag		
Device Health Report		
Field FW Update		\checkmark
Production State Awareness	\checkmark	\checkmark
CMD Queuing		\checkmark



THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE

©2021 Kingston Technology Corporation, 17600 Newhope Street, Fountain Valley, CA 92708 USA. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. Printed in the USA MKF-624.4US

