





PANEL MOUNTING



CONTACT ARRANGEMENT

code for x	function	actuator position/connected terminals	
D	On-On (alternating)	Pos.1: 1-2, 4-5, 7-8	Pos. 2: 2-3, 5-6, 8-9
F	Mom-On	Rest position: 1-2, 4-5, 7-8	Pressed down: 2-3, 5-6, 8-9

Specifications:

Contact rating:	3A, 250V AC / 6A, 125V AC 4A, 30V DC / 5A, 12V DC 6A, 6V DC
Contact resistance:	20mOhm max.
Insulation resistance:	1 000MOhm min. at 500V DC
Dielectric strength:	1 500V, 50Hz for the duration of 1 minute
Operating temperature:	-45°C to +140°C
Mechanical life:	min. 30 000 cycles
Soldering conditions:	hand-soldering: max.: 420°C, 3sec., 60W auto-soldering: max.: 270°C, 5sec.
Mounting instruction:	max. torque: 49Ncm
IP rating:	IP67
Material:	Terminal / contact: brass, silver plated Case: DAP Housing: stainless steel, CNS9265 Bushing: copper alloy, C3604BD nickel plated Actuator: copper alloy, C3604BD chrome plated
Included accessories:	1 pc. nut M6x0.75, nickel plated, 9mm wrench size 1 pc. tooth washer 1 pc. O-ring, silicone



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm			Date	Name	MPE 306 x	
			07/09	dr		
					30 18 81	
Dimension	01/11	dr	knitter-switch			Page
Modifications	Date	Name				1/1