






P.C.B. LAYOUT



CIRCUIT DIAGRAM




Tolerances: ±0.20mm			Date	Name	TSSE 610 x-RA-1	
			05/08	dr		
Revised	04/12	dr	knitter-switch			Page 1/2
Travel	08/10	dr				
Revised	05/10	dr				
Modifications	Date	Name				

30 14 84

Specifications:

Contact rating: 50mA, 12V DC
Contact resistance: 100mOhm max.
Insulation resistance: 100MOhm min. at 500V DC for 1 minute
Dielectric strength: 250V AC (50Hz or 60Hz) for 1 minute
Operating temperature: -40°C to +85°C
Storage temperature: -40°C to +85°C
Mechanical life: 500 000 cycles
Travel: 0.45 +/-0.2mm
Material: Cover: nickel silver
Sealed rubber: silicone rubber hardness: 70°-60°
Contact: phosphor bronze, silver plated
Terminal: brass, silver plated
Base: high-temp. thermoplastic PA9T UL94V-0, molded black

Soldering conditions:



x	Operating force (gf)	Stem colour
R	260 +/-70	red
N	180 +/-50	brown
RK	260 +/-70	black
NK	180 +/-50	black



Tolerances: ±0.20mm			Date	Name	TSSE 610 x-RA-1
			05/08	dr	
			knitter-switch		30 14 84
Modifications	Date	Name	Page		
			2/2		