



W-CDMA

1xEV-DO

TDMA

WiMAX™

Bluetooth

802.11 WLAN

NFC / EMV Test

MIMO

ZigBee

cdma2000® / CDMA

**Wireless Connectivity** 

Internet of Things (IoT)

Ultra-Wideband (UWB)

Digital Video - DVB

GNSS & A-GNSS

Multi Standard Radio (MSR)

TD-SCDMA

GSM, GPRS, EGPRS & EDGE/Evo









 $\odot$ 



## Careers





Solar Micro Inverter Testing Solar Cells & Modules

Batteries

MEMS & NEMS Devices

Power Electronics

Amplifiers

Mixers, Frequency Converters

Oscillators Antennas Filters

Printed Circuit Boards

Device Modeling and Characterization Base Transceiver Station Filter & Duplexer

Handset Filter & Duplexer Handset Antennas Test

MIPI Design & Tests

PCI Express (PCIe)

Pulse Amplitude Modulation (PAM-4) Design and Test

**(III)** 

Serial ATA (SATA) and Serial Attached SCSI (SAS &

SAS 2) Design and Test USB and Type-C™ Cable and Connector

## RF & Microwave

RF & Microwave Design

X-Parameters

Passive Intermodulation (PIM) Noise Figure Measurements Design & Test Integration Pulsed-RF Measurements

EMI & EMC Simulations, Measurements, and

Precompliance Testing Signal Monitoring, Geolocation Impedance and Impedance Matching

ESL Design Phase-Locked Loops Portable Field Test

### **Education Corner**

University Research Resources

Teaching Resources Student Resources

# **Optical & Photonic**

Optical & Photonic

#### Overview & **Features**

Options & Accessories Document Library

# **Key Features & Specifications**

- · 40 Channel Single-Ended Multiplexer
- Single-wire switching for common-low applications
- 60 ch/s scanning
- Built-in thermocouple reference junction

# Description

Use the Keysight 34908A module for the 34970A/34972A Data Acquisition/Switch Unit for the greatest density in common-low applications, such as battery test, component characterization, and benchtop testing. Each module switches 40 one-wire inputs. All two-wire internal measurements except current are supported. The module low connection is isolated from earth and can float up to 300 V.

## **Standard Product Includes:**

- 1 34908A, 40-Channel Single-Ended Multiplexer Module
- 1 Certificate of Calibration





# Product Support Center

- **Technical Support** manuals, drivers, application notes, firmware, software, ...
- Parts
- · Repair & Calibration Services



# Training & Events

· All Webcast On-Demand Recordings

myKeysight	Buy	Support Tasks	Legal
My Products	How to Buy or Rent	Register your Product	Privacy
My Watchlist	Request a Quote	Find a Manual	Terms
My Download History	Find a Partner	Update Firmware/Software	Trademark Acknowledgements
My News	See Special Offers	Browse Application Notes	
	Check Order Status	Request Repair or Calibration	
	View Trade-In Offers	Check Warranty Status	
	Browse Used Equipment	View Discussion Forums	
	Why Buy Keysight	Find a Part	
© Keysight Technologies 2000-2016	Feedback   Contact Keysi	ght   Agilent.com	