



Item	Material	Finish
①	PBT+15%GF	BLACK
②	BRASS	NICKEL PLATED
③	P-BRONZE	NICKEL PLATED
④	P-BRONZE	NICKEL PLATED
⑤	PE	BLACK

Part Number	Center Post Diameter
KLDX-PA-0202-A-LT	2.10mm
KLDX-PA-0202-B-LT	2.60mm

**Electrical Specifications**

Insulation Resistance:  
100 megohms at 500V DC

Contact Resistance:  
30 milliohms max.

Dielectric Withstanding Voltage:  
500V for 1 minute

Rated Current: 5A

Rated Voltage: 30V DC

Tolerances
X.X ± 0.35
X.XX ± 0.25
Unless Stated
Otherwise

**RoHS COMPLIANT**

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	09/02/11	New Drawing	S. Vien	H. MA	S. Vien	08/30/11
A1	10/24/11	Release Drawing	H. MA	N/A		
A2	05/07/12	Remove CSA	S. Vien	C. Kelleher		UNITS
A3	01/16/13	ECO #12-063	S. Vien	P. DalCanto		
A4	06/13/18	ECO #18-029	G. Serrato	D. Shehan		
A5	02/19/19	ECO #19-016	G. Serrato	D. Shehan		

**KLDX-PA-0202-x-LT**

DC Power Plug, With Over Mold, RoHS Compliant

2.1mm, 2.6mm Diameter, Locking Type

