




28B2400-000- BROADBAND CYLINDRICAL CORES



BROADBAND SOLID FERRITE CORES FOR ROUND CABLES AND WIRING HARNESSSES

Laird's Cylindrical EMI suppression ferrites provide a cost effective means of reducing common and differential mode EMI. These cores are most frequently used to suppress common mode EMI on the internal and external cable assemblies of electronic equipment. By decreasing the levels of EMI radiated by internal cables, ferrite cores can reduce the cost and amount of overall shielding required to confine EMI within a product's enclosure. They may also be successfully used on power cables that carry digital or analog signaling. To achieve maximum EMI filtering performance in a given application, select a ferrite with an inner diameter most

closely matching the outer diameter of the wire or wire bundle to be filtered. The in-circuit impedance may be substantially increased by passing 2 turns of the wire conductor through the ferrite core. A typical common mode application might have two conductors passed through a ferrite core. With equal and opposite currents flowing through the core, zero net bias is established through the component, and maximum impedance is thus realized from the ferrite.



Prototyping Available



Custom Solutions



Standard Stock



Samples Available

Features

Suitable for applications from 30 MHz ~ 1 GHz

Available in variety of sizes, custom design also available

Specifications

Additional Product Description Lead Free Standard Catalog Part	Applications Cables and wiring harnesses, USB Cables, Consumer Electronics, Energy & Utilities, Security
Dimension A 2.400in (60.96mm)	Dimension A (inches) 2.40
Dimension A (mm) 60.96	Dimension B 1.4in (35.56mm)
Dimension B (inches) 1.40	Dimension B (mm) 35.56
Dimension C 0.5in (12.7mm)	Dimension C (inches) 0.50
Dimension C (mm) 12.70	Figure Number 1
Industries Automotive, Healthcare / Medical, Industrial / Production, Computer / Gaming, Telecom, Transportation	Material Type Broad Band Material
Nominal Z Ohms at 100 MHz 135	Part Size Code 2400

Product Line

Round and Cylindrical Cores

Typical Impedance (Ω) @ 25 MHz

60