

NANOBLADE Internal Wireless Device Antenna 2400-2500 MHz/4900-6000 MHz



The evolution of technology has brought the need to communicate everywhere and at all times without being confined to one space. Lairds' internal wireless device antennas feature wide bandwidth to enhance the performance and application of portable wireless devices based on standards such as 802.11 and Bluetooth®. The antennas are specifically designed to be embedded inside devices for aesthetically-pleasing integration with high durability.

FEATURES AND BENEFITS

- Covers 2.4 to 2.5 GHz and 4.9 to 6 GHz for all WLAN applications
- Coaxial cable pigtail with various connector choices
- Omnidirectional patterns and all frequencies with increased gain in upper bands for optimal coverage
- Conformance to European RoHS Directive

SPECIFICATIONS						
Part Numbers	CAF94504, CAF94505, MAF95056, MAF95090			ENB2449A1-10MHL4		
Operating Frequency (MHz)	2400-2500	5150-5350	5600-6000	2400-2500	5150-5350	5600-6000
Gain (dBi)	2	3.9	4	3.19	4.1	4.35
VSWR – Max	2:1					
Nominal Impedance (Ohms)	50					
Polarization	Vertical, Omnidirectional					
Dimensions – cm (in.)	5.08 x 1.65 (2.0 x 0.65)					
Material Substance Compliance	RoHS					
Operating Temperature – °C (°F)	-30 to +70 (-22 to +158)					
Storage Temperature – °C (°F)	-40 to +85 (-40 to +185)					

CONFIGURATION

PART NUMBER	CABLE LENGTH	CONNECTOR
CAF94504	175 mm, RG-178	RA-MMCX
CAF94505	100 mm, Ø 1.13 mm	IPEX MHF
MAF95056	100 mm, RG-178	Flying lead
MAF95090	175 mm, Ø 1.13 mm	IPEX MHF
ENB2449A1-10MHL4	100 mm, Ø 1.13 mm	IPEX MHF4L

RADIATION PATTERNS



RoHS

sales@lairdconnect.com support@lairdconnect.com www.lairdconnect.com Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original ate of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability of sublicity of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2020 Laird Connectivity, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

