






THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	2/23/18	D.FRISIELLO



MODEL NUMBER	LENGTH FEET [METERS]
TRA5261S-1F	1.0 [.30]
TRA5261S-2F	2.0 [.61]
TRA5261S-3F	3.0 [.91]
TRA5261S-5F	5.0 [1.52]
TRA5261S-10F	10.0 [3.05]
TRA5261S-15F	15.0 [4.57]
TRA5261S-25F	25.0 [7.62]
TRA5261S-50F	50.0 [15.24]
TRA5261S-75F	75.0 [22.86]
TRA5261S-100F	100.0 [30.48]
TRA5261S-125F	125.0 [38.10]
TRA5261S-150F	150.0 [45.72]
TRA5261S-175F	175.0 [53.34]
TRA5261S-200F	200.0 [60.96]

4TP, CAT 5e, 26AWG STRANDED SILVER PLATED COPPER WITH ALUM/POLY FOIL SHIELD AND ROUND TINNED PLATED COPPER BRAID, (85% MIN. COVERAGE). JACKET: FEP, BLUE
 OPERATING TEMPERATURE RANGE: -55 °C TO +150 °C
 NOM. DIA: .205 [5.21], MIN. BEND RAD: 1.0" [25.4]



NOTES:

- FIRE PROPERTIES: (FST)
 MEETS OR EXCEEDS THE APPLICABLE REQUIREMENTS OF FAR 25.869, FAR 25.853, ABD0031, AND D6-51377.
- LENGTHS OVER 10 METERS (32.8 FT) ARE CHANNEL RATED.
 - PLUG CONFORMS TO TIA-1096.
 - CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
 - CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM PACKAGING SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:
 CE2011/65/EU (RoHS DIRECTIVE)

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +5% / -0%	APPROVALS	DATE	 50 HIGH STREET NORTH ANDOVER, MA 01845				
	DRAWN BY D.FRISIELLO	2/22/18					
ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5.08] .XX = ±.02 [5.1] .XXX = ±.005 [1.3]	CHECKED BY D.GUITADAURO	2/23/18	CATEGORY TELECOM/MODULAR				
	APPROVED BY D.GUITADAURO	2/23/18	PRODUCT DESCRIPTION C5e SF/UTP 26STR FEP BLU +150° SLIM				
PROJECTION 	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	COLOR VARIATIONS MAY OCCUR	<table border="1"> <tr> <td>SIZE A</td> <td>FSCM NO. 43321</td> <td>DWG. NO. TRA5261S</td> <td>REV. A</td> </tr> </table>	SIZE A	FSCM NO. 43321	DWG. NO. TRA5261S	REV. A
SIZE A	FSCM NO. 43321	DWG. NO. TRA5261S	REV. A				
SCALE: NONE		CAD FILE: TRA5261S.SLDDRW	SHEET 1 OF 1				