





	Item #	Description		1-9	10-24	25-99	100+
п	Itom #	Doscription		1 0	10 24	20-00	1001

# D-Sub Metal Hood Kits - Choice of Five Grommets to Satisfy all Size Requirements

Cast alloy metal construction with a matte nickel plate finish over tin and copper for the best conductivity. Kit includes a set of five grommets and 4-40 thread mounting screws.

SDC9AG	Assembled Hood Kit, DB9 Metal	2.60	2.44	2.29	CALL
SDC15AG	Assembled Hood Kit, DB15 Metal	3.65	3.43	3.21	CALL
SDC25AG	Assembled Hood Kit, DB25 Metal	3.90	3.67	3.43	CALL
SDC37AG	Assembled Hood Kit, DB37 Metal	5.15	4.84	4.53	CALL
SDC50AG	Assembled Hood Kit, DB50 Metal	5.45	5.12	4.80	CALL

## 4-40 Thumbscrews for SDC Metal and Plastic D-Sub Hood Kits

Nickel plated steel, knurled, slotted thumbscrews are now available for the entire SDC family of D-Sub hoods

SDC Thumbscrew, 4-40 Thread 0.40 0.37 0.34 CALL

## Right Angle D-Sub Metal Hood Kits-Low Profile with Thumbscrews

Right angle hoods offered for applications requiring a 90 degree cable exit. Cast alloy metal construction with a nickel plated finish Right Angle Assembled Hood Kit, DB9 Metal SDRA9AG 4.15 3.90

3.65 CALL Right Angle Assembled Hood Kit, DB15 Metal CALL 4.40 3.87 SDRA25AG Right Angle Assembled Hood Kit, DB25 Metal 4.65 4.37 4.09 CALL

#### Replacement Grommets for SDC and SDRA Metal Backshells

These grommets are the same as supplied with the SDC and SDRA metal backshell kits. Five different sizes are offered per backshell size to best

GROM-9&15 GROM-25 GROM-37&50	Replacement Grommets, SDC & SDRA 9/15 Metal Backshells Replacement Grommets, SDC & SDRA 25 Metal Backshells Replacement Grommets, SDC 37/50 Metal Backshells	0.75 0.75 0.90	0.69 0.69 0.83	0.63 0.63 0.76	CALL CALL CALL
4-40 Hex Jack S	Screws-Difficult to Find Hardware for Mounting D-Sub Connec	ctors			
SDG250 SDG300 SDG400 SDG400S SDG400XS SDG450XS SDG500	Jack Screw Kit, .25 inch (0.6cm) Thread, .232 inch (0.6cm) Screwlock, Pkg/50 Jack Screw Kit, 30 inch (0.8cm) Thread, .232 inch (0.6cm) Screwlock, Pkg/50 Jack Screw Kit, .40 inch (1.0cm) Thread, .232 inch (0.6cm) Screwlock, Pkg/50 Jack Screw Kit, .40 inch (1.0cm) Thread, .197 inch (0.5cm) Screwlock, Pkg/50 Jack Screw Kit, .40 inch (1.0cm) Thread, .160 inch (0.4cm) Screwlock, Pkg/50 Jack Screw Kit, .45 inch (1.1cm) Thread, .160 inch (0.4cm) Screwlock, Pkg/50 Jack Screw Kit, .50 inch (1.3cm) Thread, .232 inch (0.6cm) Screwlock, Pkg/50	14.45 14.45 14.45 14.45 14.45 14.45 14.45	13.58 13.58 13.58 13.58 13.58 13.58 13.58	12.72 12.72 12.72 12.72 12.72 12.72 12.72	CALL CALL CALL CALL CALL CALL CALL
Hex Standoff 4-	Hex Standoff 4-40 Thread - Needed with Hood Kits to Convert Male to Female				
SDH SDHS SDH-160	Hex Standoffs, .232 inch (0.6cm) Hex, Pkg/50 Hex Standoffs, .195 inch (0.5cm) Hex, Pkg/50 Hex Standoffs, .160 inch (0.4cm) Hex, Pkg/50	9.85 9.85 9.85	9.26 9.26 9.26	8.67 8.67 8.67	CALL CALL CALL
4-40 Screw and Retainer Pair - For Use on Male D-Sub Connectors with Metal Tabs					
SDF1	Screws and Retainers, Chromate, Pkg/50	13.80	12.97	12.14	CALL
4-40 Screw and Guard - Replacement for Cable Connector Hoods Such as SDC Series					
SDK	Screws and Guards, Nickel Plate, Pkg/50	6.30	5.80	5.29	CALL

## Stainless Wall Plates - Accept a Variety of D-Sub Connectors

Wall plates that accept common D-Sub connectors are found to be useful by many installers.

WPD109	Stainless Wall Plate, One DB9/HD15 Opening	2.75	2.59	2.42	CALL
WPD115	Stainless Wall Plate, One DB15/HD26 Opening	2.75	2.59	2.42	CALL
WPD125	Stainless Wall Plate, One DB25/HD44 Opening	2.75	2.59	2.42	CALL

### Rotary Cable Stripper - Cuts Cable Jackets

These tools offer an economical and consistent cable jacket strip every time. Featuring easy to adjust cutting depth, these tools strip both around the cable perimeter and lengthwise. RCS10 strips cable jackets ranging from 0.125" (0.3cm) to 1.0" (2.5cm). MK02 strips cable jackets ranging from 0.18" (0.5cm) to 1.12" (2.8cm). Choose RCS10 for light duty use and MK02 for heavier duty use.

Round Cable Stripper CALL 33.76 33.07

# **Cable Ties and Cable Mounts**

Cable ties come in handy to secure cable assemblies in different applications. Four different sizes, in packages of 100 pieces each. Color is black. Cable tie mounts allow the user to secure wire and/or cable quickly and easily to a surface. Mounts can be secured with screws or adhesive. Material is UL94V-2 rated nylon, color is black.

6 inch (20.3cm) Cable Ties, Pkg/100	8.00	7.52	7.04	CALL
8 inch (15.2cm) Cable Ties, Pkg/100	9.15	8.60	8.05	CALL
8.5 inch (21.6cm) Cable Ties, Pkg/100	10.30	9.68	9.06	CALL
11.5 inch (29.2cm) Cable Ties, Pkg/100	11.45	10.76	10.08	CALL
Black Cable Tie Mount, 0.75" (1.9cm), Pkg/10	4.35	4.00	3.65	CALL
Black Cable Tie Mount, 1.50" (3.8cm), Pkg/10	8.35	7.68	7.01	CALL
	8 inch (15.2cm) Cable Ties, Pkg/100 8.5 inch (21.6cm) Cable Ties, Pkg/100 11.5 inch (29.2cm) Cable Ties, Pkg/100 Black Cable Tie Mount, 0.75" (1.9cm), Pkg/10	8 inch (15.2cm) Cable Ties, Pkg/100 9.15   8.5 inch (21.6cm) Cable Ties, Pkg/100 10.30   11.5 inch (29.2cm) Cable Ties, Pkg/100 11.45   Black Cable Tie Mount, 0.75" (1.9cm), Pkg/10 4.35	8 inch (15.2cm) Cable Ties, Pkg/100 9.15 8.60   8.5 inch (21.6cm) Cable Ties, Pkg/100 10.30 9.68   11.5 inch (29.2cm) Cable Ties, Pkg/100 11.45 10.76   Black Cable Tie Mount, 0.75" (1.9cm), Pkg/10 4.35 4.00	8 inch (15.2cm) Cable Ties, Pkg/100 9.15 8.60 8.05   8.5 inch (21.6cm) Cable Ties, Pkg/100 10.30 9.68 9.06   11.5 inch (29.2cm) Cable Ties, Pkg/100 11.45 10.76 10.08   Black Cable Tie Mount, 0.75" (1.9cm), Pkg/10 4.35 4.00 3.65

# Expandable Sleeving - Pkg / 100ft (30.5m), Polyester Material with VW-1 Flammability Rating

Polyester expandable flexible tubing is ideal for protecting wire and/or cable. The open weave design allows for flexible routing, high resistance to abrasion and broad range of expansion. Available in .125" (0.3cm), .25" (0.6cm) and .5" (1.3cm) diameters, color is black with white tracer.

Item #	Description			Lis	t Price	
TUBEXP-0.25 TUBEXP-0.5	Expandable Braid Sleeving, .25" (0.6cm) Diameter, 100ft (30.5m) Expandable Braid Sleeving, .5" (1.3cm) Diameter, 100ft (30.5m)	28.20 38.55	25.94 35.47	23.69 32.38	CALL CALL	
TUBEXP-0.125	Expandable Braid Sleeving, .125" (0.3cm) Diameter, 100ft (30.5m)	22.45	20.65	18.86	CALL	

# 3M Heat Shrink Tubing Kits

3M's popular kits are versatile assortments of flexible polyolefin heat shrink tubing used in a variety of electronic and electrical applications. Each kit is packaged in a plastic box.

SPVFP301-BLK	Heat Shrink Kit, Black Colors	60.85
SPVFP301-ASST	Heat Shrink Kit, Assorted Colors	60.85
3M Copper Foil Shi	elding Tape with Conductive Adhesive	

TAP1181-3/8	Copper Foil Shielding Tape, 2.6 MIL x 3/8 inch (1.0cm) W x 18 Yards (16.5m)	16.30
TAP1181-3/4	Copper Foil Shielding Tape, 2.6 MIL x 3/4 inch (1.9cm) W x 18 Yards (16.5m)	32.05