

HGG.TT.304.CLLPV

SUMMARY

Wires

Low	4	101-169
High	0	
Coax	0	Image is for illustrative purpose only
Triax	0	Download
Quad	0	Request a quote
Fiber	0	Catalog
Fluidic	0	<u>v</u>
Series	TT	
Termination type	Female solder	
IP rating	68	
Cable Ø	0.00 - 0.00 mm	
Matching parts		
Status	active	
Alternative part		

TECHNICAL DETAILS

Mechanics

Shell Style/Model	HG*: Fixed socket, nut fixing, watertight or vacuumtight
Keying	1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Cable Fixing	: 0 - 0 mm
Variant	PV : Watertight / Vacuum-tested

Performance

Configuration	T.304 : 4 Low Voltage			
Insulator				
Rated Current	2 Amps			

Specifications

Contact Type: Solder Vtest: 650 V (DC)500 V (AC)


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

Temp (min / max): -55°C / +200°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Salt Spray Corrosion: >144 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) R leak (He) (max): 0.0000001 mbar*l/s (if vacuum-tested) IP Rating: 68

DRAWINGS

Draws





0°



Dimensions

	А	В	С	E	L	Μ	Ν	e
mm.	10	6.4	7.1	5.5	18	1.2	15.0	M7x0.5
in.	0,39	0,25	0,28	0,22	0,71	0,05	0,59	

RECOMMENDED BY LEMO

Tools

None

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.