

### **SUMMARY**

#### # Wires

 Low
 0

 High
 0

 Coax
 0

 Triax
 0

 Quad
 0

 Fiber
 0

 Fluidic
 0

Series 00

Termination type No contacts / Accessory

IP rating 0

**Cable Ø** 2.80 - 3.10 mm

**Status** active

Alternative part



Image is for illustrative purpose only

#### **Download**

Request a quote

Catalog

### **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model GMD\*: Bend relief Red

**Keying** No keying

Housing Material Thermoplastic polyurethane elastomer (Desmopan 786)

Variant R : Red Weight .29 g

#### **Performance**

Configuration

Insulator

**Rated Current** 


#### **Others**

IP Rating: 0

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## **DRAWINGS**

#### **Draws**



# No keying

#### **Dimensions**

	А	L
mm.	2.8	22
in.	0.11	0.87

## **RECOMMENDED BY LEMO**

**Tools** 

None

**Cables** 

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.