

# LINEAR TECHNOLOGY MATERIALS DECLARATION

LT83911UFD#PBF

(Engineering Calculation)

QFN 4mm X 5mm Exp. Pad

(printed on: 2017-12-03 11:13:47)

**TOTAL MASS (g): 0.049268**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.001760	1000000	35722.8320312		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.019997	975000	405880.40625		
		Iron (Fe)	7439-89-6	0.000492	24000	9986.15527344		
		Phosphorus (P)	7723-14-0	0.000006	300	121.78238678		
		Zinc (Zn)	7440-66-6	0.000014	700	284.158905029		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.020509</b>	<b>1000000</b>	<b>416272.53125</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.000227	1000000	4611.65527344		
		<b>External Plating Total:</b>				<b>0.000227</b>	<b>1000000</b>	<b>4611.65527344</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000429	1000000	8707.44042969		
		<b>Internal Plating Total:</b>				<b>0.000429</b>	<b>1000000</b>	<b>8707.44042969</b>
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.000841	750000	17069.8320312		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000280	250000	5683.17822266		
<b>Die Attach Total:</b>				<b>0.001121</b>	<b>1000000</b>	<b>22753.0097656</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.003244	130000	65843.6796875		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.021457	860000	435514.09375		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000000	0	0		

		Carbon Black (C)	1333-86-4	0.000250	10000	5074.26611328
		<b>Encapsulation Total:</b>		<b>0.024951</b>	<b>1000000</b>	<b>506432.0625</b>
<b>Bond Wire Estimated</b>	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	<b>0.000271</b>	<b>1000000</b>	<b>5500.50439453</b>
				<b>TOTAL MASS (g):</b>		<b>0.049268</b>