

# LINEAR TECHNOLOGY MATERIALS DECLARATION

LT3055IMSE-3.3#TRPBF

(Engineering Calculation)

MSOP-Exposed

(printed on: 2017-12-03 09:59:56)

**TOTAL MASS (g): 0.036873**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.002332	1000000	63244.0664062		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.013845	975000	375477.75		
		Iron (Fe)	7439-89-6	0.000341	24000	9247.953125		
		Phosphorus (P)	7723-14-0	0.000004	300	108.480384827		
		Zinc (Zn)	7440-66-6	0.000010	700	271.200958252		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.014200</b>	<b>1000000</b>	<b>385105.375</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.000710	1000000	19255.9453125		
		<b>External Plating Total:</b>				<b>0.000710</b>	<b>1000000</b>	<b>19255.9453125</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000086	1000000	2332.32836914		
		<b>Internal Plating Total:</b>				<b>0.000086</b>	<b>1000000</b>	<b>2332.32836914</b>
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.000395	820000	10712.4394531		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000087	180000	2359.44848633		
<b>Die Attach Total:</b>				<b>0.000482</b>	<b>1000000</b>	<b>13071.8867188</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.002439	130000	66145.921875		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.015571	830000	422287.0625		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000657	35000	17817.9023438		

		Carbon Black (C)	1333-86-4	0.000094	5000	2549.28930664
		<b>Encapsulation Total:</b>		<b>0.018761</b>	<b>1000000</b>	<b>508800.15625</b>
<b>Bond Wire Estimated</b>	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	<b>0.000302</b>	<b>1000000</b>	<b>8190.26953125</b>
				<b>TOTAL MASS (g):</b>		<b>0.036873</b>