FEATURES

* 1.4 inch (35.76 mm) MATRIX HEIGHT.
* LOW POWER REQUIREMENT.
* SINGLE PLANE, WIDE VIEWING ANGLE
* SOLID STATE RELIABILITY.
* 5x8 ARRAY WITH X-Y SELECT.
* COMPATIBLE WITH USASCLL AND EBCDIC CODES.
* STACKABLE HORIZONTALLY.
* CATEGORIZED FOR LUMINOUS INTENSITY.

DESCRIPTION

The LTP-14958AA is a 1.4 inch (35.76 mm) height dot matrix display. This device is multicolor applicable display, which has gray face and white dot color. The red orange LED chips are made from GaAsP on a transparent GaP substrate. The green LED chips are made from GaP on a transparent GaP substrate.

DEVICE

PART NO.	DESCRIPTION
Red Orange & Green	Cathode Column
LTP-14958AA	Anode Row

PACKAGE DIMENSIONS



NOTES: All dimensions are in millimeters. Tolerances are± 0.25 mm (0.01“) unless otherwise noted.

INTERNAL CIRCUIT DIAGRAM



PIN CONNECTION

No.	CONNECTION
1	CATHODE COLUMN 1 (GREEN)
2	CATHODE COLUMN 1 (RED ORANGE)
3	CATHODE COLUMN 2 (GREEN)
4	CATHODE COLUMN 3 (GREEN)
5	ANODE ROW 5
6	ANODE ROW 7
7	ANODE ROW 8
8	ANODE ROW 6
9	CATHODE COLUMN 5 (RED ORANGE)
10	CATHODE COLUMN 5 (GREEN)
11	CATHODE COLUMN 4 (GREEN)
12	CATHODE COLUMN 4 (RED ORANGE)
13	CATHODE COLUMN 3 (RED ORANGE)
14	ANODE ROW 3
15	ANODE ROW 2
16	CATHODE COLUMN 2 (RED ORANGE)
17	ANODE ROW 4
18	ANODE ROW 1

ABSOLUTE MAXIMUM RATING AT T_A=25°C

PARAMETER	GREEN	RED ORANGE	UNIT
Average Power Dissipation Per Dot	36		mW
Peak Forward Current Per Dot	100		mA
Average Forward Current Per Dot	13		mA
Derating Linear From 25°C Per Dot	0.17		mA/°C
Reverse Voltage Per Dot	5		V
Operating Temperature Range	-35°C to +85°C		
Storage Temperature Range	-35°C to +85°C		
Solder Temperature 1/16 inch Below Seating Plane for 3 Seconds at 260°C			

ELECTRICAL / OPTICAL CHARACTERISTICS AT T_A=25°C

GREEN

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I_V	1780	4800		μcd	I_p=80mA 1/16DUTY
Peak Emission Wavelength	λp		565		nm	I_F=20mA
Spectral Line Half-Width	Δλ		30		nm	I_F=20mA
Dominant Wavelength	λd		569		nm	I_F=20mA
Forward Voltage any Dot	V_F		2.1	2.6	V	I_F=20mA
			3	3.7	V	I_F=80mA
Reverse Current any Dot	I_R			100	μA	V_R=5V
Luminous Intensity Matching Ratio	I_V-m			2:1		I_p=80mA 1/16DUTY

RED ORANGE

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I_V	1780	4800		μcd	I_p=80mA 1/16DUTY
Peak Emission Wavelength	λp		630		nm	I_F=20mA
Spectral Line Half-Width	Δλ		40		nm	I_F=20mA
Dominant Wavelength	λd		621		nm	I_F=20mA
Forward Voltage any Dot	V_F		2	2.6	V	I_F=20mA
			2.6	3.4	V	I_F=80mA
Reverse Current any Dot	I_R			100	μA	V_R=5V
Luminous Intensity Matching Ratio	I_V-m			2:1		I_p=80mA 1/16DUTY

Note: Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commision Internationale De L'Eclairage) eye-response curve.

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES

(25°C Ambient Temperature Unless Otherwise Noted)



Fig1. RELATIVE INTENSITY VS. WAVELENGTH



Fig2. RELATIVE LUMINOUS EFFICIENCY (LUMINOUS INTENSITY PER UNIT CURRENT) VS. PEAK CURRENT (REFRESH RATE 1KHz)



Fig3. FORWARD CURRENT VS. FORWARD VOLTAGE



Fig4. RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT



Fig5. MAX. AVERAGE FORWARD CURRENT VS. AMBIENT TEMPERATURE.



Fig6. MAX. PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE 1KHz)

NOTE: G=GREEN & E=RED ORANGE