

**SURFACE MOUNT
GLASS PASSIVATED RECTIFIERS**

**REVERSE VOLTAGE –400 to 1000 Volts
FORWARD CURRENT – 8.0 Amperes**


FEATURES

- Glass passivated chip
- For surface mounted applications
- Low reverse leakage current
- Low forward voltage drop
- High current capability
- Plastic material has UL flammability classification 94V-0

MECHANICAL DATA

- Case: Molded plastic
- Case Material molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl.) "Halogen-free".
- Polarity: Color band denotes cathode
- Weight : 0.007 ounces, 0.21 grams

SMC



SMC		
DIM.	MIN.	MAX
A	6.60	7.11
B	5.59	6.22
C	2.92	3.18
D	0.15	0.31
E	7.75	8.13
F	0.05	0.20
G	2.01	2.50
H	0.76	1.52
All dimension in millimeter		

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

ABSOLUTE RATINGS

PARAMETER	SYMBOL	S8GC	S8JC	S8KC	S8MC	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	400	600	800	1000	V
Maximum DC blocking voltage	V_{DC}	400	600	800	1000	V
Maximum average forward rectified current @ $T_L=75^\circ\text{C}$	$I_{(AV)}$	8.0				A
Peak forward surge current single half sine-wave superimposed on rated load. (JEDEC METHOD)@ 8.3ms	I_{FSM}	200				A
Peak forward surge current single half sine-wave superimposed on rated load. (JEDEC METHOD)@ 1.0ms	I_{FSM}	450				A
Typical junction capacitance (Note1)	C_J	45				pF
Operation and storage temperature range	T_J, T_{STG}	-55 to +150				°C

STATIC ELECTRICAL CHARACTERISTICS

PARAMETER	TEST CONDITIONS		SYMBOL	MAX.	UNIT
Forward voltage	$I_F=8.0A$	$T_J=25^\circ\text{C}$	V_F	0.985	V
Leakage current	VR rated	$T_J=25^\circ\text{C}$ $T_J=125^\circ\text{C}$	I_R	10 250	uA

THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	TYP.	UNIT
Typical thermal resistance (Note2)	R_{thJA}	15	°C/W
Typical thermal resistance	R_{thJC}	6	°C/W
	R_{thJL}	8	
	R_{thJA}	60	

DYNAMIC ELECTRICAL CHARACTERISTICS

PARAMETER	TEST CONDITIONS	SYMBOL	TYP.	UNIT
Reverse recovery time	$I_F=0.5A, I_{rr}=0.25A, I_R=1.0A$	T_{RR}	2700	ns

Note :

- (1) Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
- (2) Thermal resistance junction to Ambient. in accordance with JESD-51. Unit mounted on 100mm*100mm*1.7mm copper pad, heatsink

**RATING AND CHARACTERISTIC CURVES
S8GC thru S8MC**



FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 - TYPICAL FORWARD CHARACTERISTICS





FIG.4 - TYPICAL REVERSE CHARACTERISTICS



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.