

51

5,08 R

Direct connectors for insert cards, pitch 2.5/2.54/5.0/ 5.08 mm



Socket board for direct mating, with solder pins




---

State: Phasing out

---

51

5,08 R



#### Environmental conditions

Temperature range -25 °C/+100 °C

#### Materials

Insulating body PPO  
Contact spring CuSn, pre-nickel and tin-plated

#### Mechanical data

Mating with Leiterplatte 1,5 ± 0,14 mm

#### Electrical data (at T<sub>amb</sub> 20 °C)

Contact resistance ≤ 3 mΩ  
Rated current 5 A  
Rated voltage 250 V AC  
Rated impulse voltage ≥ 3,0 kV

#### Associated products

##### Accessories

☞ F ☞ FD ☞ FF  
☞ FL ☞ SP 3

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
5,08 R 03	3	200	5000
5,08 R 04	4	200	5000
5,08 R 05	5	200	5000
5,08 R 06	6	200	5000
5,08 R 07	7	200	5000
5,08 R 08	8	200	5000
5,08 R 09	9	200	5000
5,08 R 10	10	200	5000
5,08 R 11	11	200	5000
5,08 R 12	12	200	5000
5,08 R 13	13	200	5000
5,08 R 14	14	200	5000
5,08 R 15	15	200	5000
5,08 R 16	16	200	5000
5,08 R 17	17	200	5000
5,08 R 18	18	200	5000
5,08 R 19	19	200	5000
5,08 R 20	20	200	5000
5,08 R 21	21	200	5000
5,08 R 22	22	200	5000
5,08 R 23	23	200	5000
5,08 R 24	24	200	5000
5,08 R 25	25	200	5000
5,08 R 26	26	200	5000
5,08 R 27	27	200	5000
5,08 R 28	28	200	5000
5,08 R 29	29	200	5000
5,08 R 30	30	200	5000
5,08 R 31	31	200	5000
5,08 R 32	32	200	5000
5,08 R 33	33	200	5000

**Packaging:**

in bulk, in a cardboard box