



Semiconductor Device Type: K7X 20 PLCC 8.9x8.9x4.4mm Matte Tin				Termination Base Alloy: Copper Alloy (Cu)			Package Homogeneous Materials: 8.1 Electronics (e.g. pc boards, displays)			J-STD-609A Product Pkg. and/or Pkg. Labeling e3																		
Basic Substance	CAS Number	Contained In Sub-Component	% Total Weight	mg/part	ppm	(mg) Total	Mold Compound	% of Total Weight	75.79																			
Silica, vitreous	60676-86-0	Mold Compound	64.422	484.256	644.215	Silica, vitreous	60676-86-0	85.00	<table border="1"> <tr><td>Silica, vitreous</td><td>60676-86-0</td><td>85.00</td></tr> <tr><td>Epoxy Resin</td><td>Trade Secret</td><td>6.13</td></tr> <tr><td>Phenolic Resin</td><td>Trade Secret</td><td>6.13</td></tr> <tr><td>Epoxy, Cresol Novolac</td><td>29690-82-2</td><td>2.45</td></tr> <tr><td>Carbon Black</td><td>1333-86-4</td><td>0.30</td></tr> <tr><td colspan="3">Total</td><td>100.00</td></tr> </table>	Silica, vitreous	60676-86-0	85.00	Epoxy Resin	Trade Secret	6.13	Phenolic Resin	Trade Secret	6.13	Epoxy, Cresol Novolac	29690-82-2	2.45	Carbon Black	1333-86-4	0.30	Total			100.00
Silica, vitreous	60676-86-0	85.00																										
Epoxy Resin	Trade Secret	6.13																										
Phenolic Resin	Trade Secret	6.13																										
Epoxy, Cresol Novolac	29690-82-2	2.45																										
Carbon Black	1333-86-4	0.30																										
Total			100.00																									
Epoxy Resin	Trade Secret	Mold Compound	4.642	34.895	46.421	Epoxy Resin	Trade Secret	6.13																				
Phenolic Resin	Trade Secret	Mold Compound	4.642	34.895	46.421	Phenolic Resin	Trade Secret	6.13																				
Epoxy, Cresol Novolac	29690-82-2	Mold Compound	1.857	13.958	18.569	Epoxy, Cresol Novolac	29690-82-2	2.45																				
Carbon Black	1333-86-4	Mold Compound	0.227	1.709	2.274	Carbon Black	1333-86-4	0.30																				
Copper	7440-50-8	Lead Frame	20.913	157.204	209.132	Total			100.00																			
Iron	7439-89-6	Lead Frame	0.514	3.867	5.144	164.55	(mg) Total	Lead Frame	% of Total Weight	21.89																		
Silver	7440-22-4	Lead Frame	0.417	3.135	4.170	Copper	7440-50-8	95.54	<table border="1"> <tr><td>Copper</td><td>7440-50-8</td><td>95.54</td></tr> <tr><td>Iron</td><td>7439-89-6</td><td>2.35</td></tr> <tr><td>Silver</td><td>7440-22-4</td><td>1.91</td></tr> <tr><td>Zinc</td><td>7440-66-6</td><td>0.13</td></tr> <tr><td>Phosphorous</td><td>7723-14-0</td><td>0.08</td></tr> <tr><td colspan="3">Total</td><td>100.00</td></tr> </table>	Copper	7440-50-8	95.54	Iron	7439-89-6	2.35	Silver	7440-22-4	1.91	Zinc	7440-66-6	0.13	Phosphorous	7723-14-0	0.08	Total			100.00
Copper	7440-50-8	95.54																										
Iron	7439-89-6	2.35																										
Silver	7440-22-4	1.91																										
Zinc	7440-66-6	0.13																										
Phosphorous	7723-14-0	0.08																										
Total			100.00																									
Zinc	7440-66-6	Lead Frame	0.027	0.206	0.274	Iron	7439-89-6	2.35																				
Phosphorous	7723-14-0	Lead Frame	0.018	0.136	0.181	Silver	7440-22-4	1.91																				
Silver	7440-22-4	Die Attach	0.125	0.943	1.255	Zinc	7440-66-6	0.13																				
Epoxy Resin	9003-36-5	Die Attach	0.045	0.335	0.445	Phosphorous	7723-14-0	0.08																				
Silicon	7440-21-3	Chip (Die)	0.610	4.585	6.100	Total			100.00																			
Gold	7440-57-5	Wire Bond	0.250	1.879	2.500	1.28	(mg) Total	Die Attach	% of Total Weight	0.17																		
Tin	7440-31-5	Plating on external leads (pins) - Matte Tin / annealed at 150°C for 1 hour	1.290	9.697	12.900	Silver	7440-22-4	73.80	<table border="1"> <tr><td>Silver</td><td>7440-22-4</td><td>73.80</td></tr> <tr><td>Epoxy Resin</td><td>9003-36-5</td><td>26.20</td></tr> <tr><td colspan="3">Total</td><td>100.00</td></tr> </table>	Silver	7440-22-4	73.80	Epoxy Resin	9003-36-5	26.20	Total			100.00									
Silver	7440-22-4	73.80																										
Epoxy Resin	9003-36-5	26.20																										
Total			100.00																									
TOTALS:			100.000	751.700	1,000,000	Epoxy Resin	9003-36-5	26.20																				
0.7517 g Total Mass						Total			100.00																			
<p>This semiconductor device and its homogenous materials comply with EU Directives: 2002/95/EC (27 January 2003) & Directive 2011/65/EU (08 June 2011) and 2015/863/EU (31 March 2015) and 2000/53/EC and 2016/774/EU (End-of-Life Vehicles (ELV) without exemption (zero)</p> <p>Compliance with the above EU Directives has been verified via internal design controls, supplier declarations, and/or analytical test data.</p> <p>If a chemical substance is absent from the list above, the chemical substance is NOT an intentional ingredient in the semiconductor device and, to the best of Microchip Technology Incorporated's knowledge and belief as of the date of this document, there is no credible reason to believe that the unavoidable impurity concentration of the chemical substance, if any, is not below the threshold of regulatory concern for any regulatory scheme world-wide.</p> <p>Molding compounds used by Microchip meet the UL94 V0 flammability standard for plastics. You can access the UL iQTM family of databases to obtain a test report at http://ul.com/global/eng/pages/offers/industries/chemicals/plastics/</p> <p>The protective "tubes" in which the specific product is shipped are made from polyvinyl chloride (PVC) plastic. "Window envelopes" used to hold the packing slip on the outer box and certain "reels" may be made from PVC plastic.</p> <p>Microchip Technology Incorporated believes the information in this form concerning substances restricted by RoHS in Microchip Technology Incorporated's semiconductor devices in their original packing materials is true and correct to the best of its knowledge and belief, as of the date listed in this form. Microchip Technology Incorporated cannot guarantee the completeness and accuracy of data in this form because it has been compiled based on the ranges provided in Material Safety Data Sheets provided by raw material suppliers. Supplier information is often protected from disclosure as trade secrets and some information may not have been provided by subcontract assemblers and raw material suppliers. Information is provided only as estimates of the average weight of these parts and the average weight of anticipated significant toxic metals components. These estimates do not include trace levels of dopants, metals, and non-metal materials contained within silicon devices (silicon IC) in the finished parts.</p> <p>Microchip Technology Incorporated does not provide any warranty, express or implied, with respect to the information provided in this declaration. The exclusive, limited product warranties provided by Microchip Technology Incorporated and its subsidiaries are contained in Microchip's standard terms and conditions of sale. These are provided in Microchip's quotations, sales order acknowledgement, and invoices.</p> <p>Microchip disclaims any duty to notify users of updates or changes to Material Content Declarations and shall not be liable for any damages, direct or indirect, consequential or otherwise, suffered by users or third parties as a result of the users' reliance on the information in Material Content Declarations (MCD) or independent third party test reports (SGS) or of this Certificate of Compliance for semiconductor products.</p> <p>Assembled package referenced above is EU REACH compliant based on the latest SVHC candidate list of ECHA which can be found at http://echa.europa.eu/web/guest/candidate-list-table</p>						4.59	Total (mg)	Chip (Die)	% of Total Weight	0.61																		
						Doped Silicon	7440-21-3	100.00	Total		100.00																	
						1.88	(mg) Total	Wire Bond	% of Total Weight	0.25																		
						Gold	7440-57-5	100.00	Total		100.00																	
						9.70	(mg) Total	Plating on external leads (pins) - Matte Tin / annealed at 150°C for 1 hour	% of Total Weight	1.29																		
						Tin	7440-31-5	100.00	Total		100.00																	

751.70

100.00