

ľ

PRODUCT NUMBER: 3117-2-00-15-00-08-0

3117-X-00-XX-00-00-08-0 Swage mount în .035 hole .020 DIA. .030 DIA.	Basic Part Number	Board Thickness	Length V
.050 DIA.	3117-1	.031	.047
	3117-2	.062	.078
	3117-3	.094	.110
	3117-4	.125	.141

DESCRIPTION

Swage Terminal Pin Current Rating: Application Specific Operating Temperature Range: -55/+125° C Mounting Feature: Swage Mount Tail Type: Soldertail Mounting Hole: .035" (0,889mm) Tail Diameter: .024" (0,610mm) Packaging: 00 - Packaged in Bulk

Shell Plating	Contact Plating	ROHS
10 μ " Gold over Nickel	No Plating on Inner Contact	RoHS-2 2011/55/EU

STANDARD TOLERANCES ON PCB TERMINAL PINS & RECEPTACLES

Diameters +/-.002" Lengths +/-.005" Angles +/- 2°

STANDARD TOLERANCES ON SPRING-LOADED PINS

Diameters +/-.002" Lengths +/-.006" Angles +/- 2°

ADDITIONAL NOTES & SPECIFICATIONS

In the interest of improved design, quality and performance, Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

© 2021 Mill-Max Mfg. Corp. 190 Pine Hollow Rd , Oyster Bay, NY 11771, USA Phone: 516.922.6000