

## PRODUCT NUMBER: 3151-2-00-01-00-08-0

3151-X-00-XX-00-00-08-0 Swage mount in .052 hole .023 DIA.	Basic Part Number	Board Thick- ness	Length A	Length V
.062 DIA.	3151-1	.031	.479	.051
	3151-2	.062	.479	.082
	3151-3	.094	.479	.113
	3151-4	.125	.479	.145

## DESCRIPTION

Swage Terminal Pin Current Rating: Application Specific Operating Temperature Range: -55/+125° C Mounting Feature: Swage Mount Tail Type: Soldertail Mounting Hole: .052" (1,321mm) Tail Diameter: .025" (0,635mm) Packaging: 00 - Packaged in Bulk

Shell Plating	Contact Plating	ROHS
200 - 300 $\mu^{\prime\prime}$ Tin/Lead over Nickel	No Plating on Inner Contact	No

## **STANDARD TOLERANCES ON PCB TERMINAL PINS & RECEPTACLES**

Diameters +/-.002" Lengths +/-.005" Angles +/- 2°

## **ADDITIONAL NOTES & SPECIFICATIONS**

In the interest of improved design, quality and performance, Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

© 2021 Mill-Max Mfg. Corp. 190 Pine Hollow Rd , Oyster Bay, NY 11771, USA Phone: 516.922.6000