


# PRODUCT NUMBER: 6618-0-07-15-00-00-03-0



#### **DESCRIPTION**

Crimp Terminal Pin

**Current Rating:** 

Application Specific A

**Operating Temperature Range:** 

-55/+125° C 🛭

**Mounting Feature:** 

Wire Mount

Wire Termination:

Crimp 16-20 AWG

Tail Type: Soldertail

**Tail Diameter:** .078" (1,981mm) **Packaging:** 07 - Packaged in Bulk

Shell Plating	Contact Plating	ROHS	

10 μ" Gold over Nickel

No Plating on Inner Contact



#### STANDARD TOLERANCES ON PCB TERMINAL PINS & RECEPTACLES

Diameters +/-.002" Lengths +/-.005" Angles +/- 2°

## STANDARD TOLERANCES ON SPRING-LOADED PINS

Diameters +/-.002" Lengths +/-.006" Angles +/- 2°

## **ADDITIONAL NOTES & SPECIFICATIONS**

In the interest of improved design, quality and performance, Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

© 2021 Mill-Max Mfg. Corp. 190 Pine Hollow Rd , Oyster Bay, NY 11771, USA Phone: 516.922.6000