

## Product Compliance Statement


December 30, 2015

Molex is committed to managing the use of chemical substances in accordance with governmental regulations, industry standards, and customer-specific requirements in order to protect the environment. For each part listed, this document provides:

- **EU RoHS Compliance Status.** EU RoHS status is declared per Directive 2011/65/EU and its subsequent amendments. Homogeneous materials of parts that are compliant to this legislation have less than 0.1% by weight each of lead, mercury, hexavalent chromium, PBB, and PBDE, and 0.01% by weight of cadmium. In situations where an exemption applies, the preceding limits, corresponding to the exempted substance(s), may be higher.

Molex's sole liability for incorrectly certifying a product shall be either replacement of the Molex product or, alternatively and in the sole discretion of Molex, return of the purchase price paid for the relevant Molex product.

For additional information regarding Molex's environmental initiatives and further explanation of this information, please visit [www.molex.com](http://www.molex.com)



Joel F. Eurich  
Director, Global Environmental, Health & Safety (EH&S)

**Table A**

Molex P/N	Part Description	RoHS Compliance Status
761551605	Impact™ 100 Ohm 4 Pair Vertical Backplane Header, Unguided, Open Endwall, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm, Lead-Free	Compliant
761601026	Impact™ 100 Ohm 4 Pair Right Angle Daughtercard Receptacle, Unguided, 16 Columns, 192 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant
761603026	Impact™ 100 Ohm 4 Pair Right Angle Daughtercard Receptacle, Left Guided, 16 Columns, 192 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant
850150165	2.54mm Pitch DIN 41612 Header, 4-Row C-Pin, Press-Fit Style R Reverse, Vertical, Through Hole, 1µm Gold (Au), 128 Circuits, Lead-Free	Compliant
197054301	PCB Tab Quick Disconnect, Male, for Wire, Box, Tab 6.35 x 0.81mm	Compliant
676430910	Universal Serial Bus (USB) Shielded I/O Receptacle, Right Angle, Type A, Black Polyester, Gold (Au) Flash, PCB Thickness 1.60mm, without Upper Flange, Lead-Free	Compliant
1061151100	EMI LC Adapter, Duplex, Metal Body, Ceramic Alignment Sleeve, Screw Mount Style	Compliant
1720640006	5.70mm Pitch, Mega-Fit® Right-Angle Header, 6 Circuits, 0.38µm Gold (Au) Plating, UL 94 V-0, Tray	Compliant
761050585	0.80mm Pitch, iPass+™ HSC, External Application, Integrated Cage and Connector Assembly, Right Angle, Press-Fit, Left Key Infiniband, 84 Circuit, 0.76µm Gold (Au) Plating, Lead-Free	Compliant
1704320002	zQuad Small Form Factor Pluggable Plus (zQSFP+™) Assembly, Surface Mount, 38 Circuit, Gold (Au) Plated 0.762µm, Supports QSFP28 / EDR	Compliant
190040005	InsulKrimp™ Fully Insulated Coupler, Male, for 14-16 AWG Wire, Box	Compliant
398501603	5.00mm Pitch Beau™ Eurostyle™ Vertical Fixed Terminal Block, 3 Circuits	Compliant
747360220	XFP Cage Assembly, 10 Gigabit Small Form Factor Pluggable Compatible, without Heat Sink or Clip, Elastomer EMI Gasket, Press-Fit Pins	Compliant
747360230	Heat Sink Clip for XFP Cage Assembly, 10 Gigabit Small Form Factor Pluggable Compatible	Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
747360242	Heat Sink for XFP Cage Assembly, 10 Gigabit Small Form Factor Pluggable Compatible, Tall Height, Power Level Up-3.5W	Compliant
747500021	QSFP+ Cage Assembly with Open Top, 2 Rear Legs, Spring Fingers, with Press-Fit Pins	Compliant
1061700150	SC Adapter, Blue Body, Ceramic Alignment Sleeve, Snap Mount Style	Compliant
1061700550	SC Adapter, Blue Body, Ceramic Alignment Sleeve, Snap Mount Style, Shutter	Compliant
1061140100	EMI MPO Adapter, Angled, Simplex, Metal Body, Single Screw Mount Style, Shutter One Side	Compliant
1061152110	EMI LC Adapter, Duplex, Metal Body, Ceramic Alignment Sleeve, Snap Mount Style, Shutter One Side	Compliant
1061241100	LC Adapter, Simplex, Blue Body, Ceramic Alignment Sleeve, Snap Mount Style, Standard Profile	Compliant
1110251203	iPass+™ High-Speed Channel (HSC) CXP Cable Assembly, 12X Quad Data Rate (QDR), 84 Circuits, 3.00m Length	Compliant with Exemption 7(c)-I
1110251205	iPass+™ High-Speed Channel (HSC) CXP Cable Assembly, 12X Quad Data Rate (QDR), 84 Circuits, 5.00m Length	Compliant with Exemption 7(c)-I
438796004	Mini-Fit® BMI Header Compliant Pin Interface, Dual Row, Vertical, 14 Circuits, Make First/Break Last, 2.54µm Tin (Sn) over Nickel Plating	Compliant
543660478	Universal Serial Bus (USB) Shielded I/O Receptacle, Surface Mount, Side Flange Reverse Mount	Compliant
190070040	Flag InsulKrimp™ Quick Disconnect, Female, for 10-12 (5.00-3.30mm <sup>2</sup> ) Wire, Box, Tab 6.35 x 0.81mm	Compliant
190170001	InsulKrimp™ Quick Disconnect, Female, for 18-22 (0.80-0.35mm <sup>2</sup> ) Wire, Box, Tab 2.79 x 0.51mm	Compliant
190700123	InsulKrimp™ Ring Tongue Terminal for 10-12 AWG Wire	Compliant
5019301100	1.25mm Pitch Duo-Clasp™ Wire-to-Board Crimp Terminal, Reel	Compliant
190040001	InsulKrimp™ Fully Insulated Coupler, Male, for 18-22 AWG Wire, Box	Compliant
760601020	Impact™ 100 Ohm 5 Pair Right Angle Daughtercard Receptacle, Unguided, 10 Columns, 150 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant

**Table A**

<b>Molex P/N</b>	<b>Part Description</b>	<b>RoHS Compliance Status</b>
760601026	Impact™ 100 Ohm 5 Pair Right Angle Daughtercard Receptacle, Unguided, 16 Columns, 240 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant
761601020	Impact™ 100 Ohm 4 Pair Right Angle Daughtercard Receptacle, Unguided, 10 Columns, 120 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free	Compliant
874370843	1.50mm Pitch Pico-SPOX™ Wire-to-Board Header, Surface Mount, Vertical, Shrouded, 8 Circuits, Embossed Tape on Reel Packaging	Compliant
190040001	InsulKrimp™ Fully Insulated Coupler, Male, for 18-22 AWG Wire, Box	Compliant